



**Roof** All-Weather Roof Repair

Fibre-reinforced bituminous repair paste

Remains soft and flexible (+20 years after application)

Also on wet and/or dry substrate

# Product

### Characteristics

• The ultimate repair for all roofs – 20-year flexibility

• Direct sealing and permanent repair at temperatures ranging from -12°C to + 50°C, on dry or wet surfaces, without having to dissolve or rinse it off.

• With butyl rubber for durability and flexibility, bitumen for waterproofing and fiberglass for strength.

### Applications

- Repair of flat and sloping roofs with bituminous roof covering.
- Sealing of chimneys, roof gutters, eaves, compression strips, roof feed-throughs, ...
- Waterproofing of foundations and walls, flat and sloping roofs, domes, terraces and balconies.
- As cold adhesive for bonding bituminous materials (roofing, shingles, corrugated panels).
- As cold adhesive for bonding together bituminous materials (roofing, shingles, corrugated sheet).
- Fixing of counter flashing.
- Immediate sealing of leaking roofs (wet substrates).

### Use

- Apply with brush on clean surface, free from snow and ice.
- Use Roof pattern to finish seams easily.
- Finish with putty knife, moistened with Tec7 Cleaner.

Use Tec7 Cleaner to clean and degrease safely, obtain the perfect finish, and to remove uncured Tec7 products.



## **Technical Info**

Flash point: 38°C (minimum). Modified asphalt content: 50 %. Solid components: 70 % Tensile strength (dry film): 200 PSI. Elongation at break (dry film): 150 %. Temperature resistance: from -40°C to +82°C. UV-resistance: very good. Climatological resistance: good. Water resistance with adequate run off: very good. Application temperature: from -12°C to +50°C. Do not apply if there is snow or ice. Shelf life: 24 months, in closed original packaging, dry, cool and frost-free For best results apply a thickness of 3 mm in layers of 1.5 mm. Consumption +/-2 kg/m<sup>2</sup> per layer of 1.5 mm

## Packing

	Article number
Roof - cartridge 310ml	602116000
Roof - cartridge 310ml	602196000
Roof - pot 1kg	602201000
Roof - pot 5kg	602204000
Roof - pot 10kg	602210000

