


WASHDOWN AND SILT TRAPS

Our pioneering range of washdown and silt traps can be used in areas such as car wash and other cleaning facilities that discharge directly into a foul drain, which feeds into a municipal treatment facility. Please note - if emulsifiers are present the discharge must not be allowed to enter an NS Class I or Class II Unit H2.



TECHNICAL INFORMATION

Product Code	Capacity (ltrs)	Max Rec. Silt (ltrs)	Max Flow Rate (l/s)	Length (mm)	Diameter (mm)	Access Shaft Diameter (mm)	Base Inlet Invert (mm)	Base to Outlet Invert (mm)	Std Fall Across Unit	Min Inlet (mm)	Std Pipework Diameter (mm)	Approx Empty (kg)
W1/010	1000	500	3	1123	1225	460	1150	1100	50	500	160	60
W1/020	2000	1000	5	2074	1225	460	1150	1100	50	500	160	120
W1/030	3000	1500	8	2952	1225	460	1150	1100	50	500	160	150
W1/040	4000	2000	11	3898	1225	460	1150	1100	50	500	160	180
W1/060	6000	3000	16	4530	1440	600	1360	1100	50	500	160	320
W1/080	8000	4000	22	3200	2020	600	2005	1955	50	500	160	585
W1/100	10,000	5000	27	3915	2020	600	2005	1955	50	500	160	680
W1/120	12,000	6000	33	4640	2020	600	2005	1955	50	500	160	770
W1/150	15,000	7500	41	5435	2075	600	1940	1890	50	500	160	965
W1/190	19,000	9500	52	6865	2075	600	1940	1980	50	500	160	1200

OVERVIEW

FEATURES AND BENEFITS

Light and easy to install

Maintenance from ground level

FACTA Class B covers
