



- **TERRACOTTA**
- **UNPOLISHED STONE AND AGGLOMERATES**



WHAT IT'S FOR

- A colour-enhancing, water and oil repellent sealer that protects outdoor surfaces in terracotta, unpolished natural stone and agglomerates.
- It protects surfaces against stains and dirt and is therefore the ideal product for use near kitchens, barbecues and on driveways where cars are parked.

ADVANTAGES

- It enhances surfaces, providing a wet look.
- It is a water-based product and so it is more environmentally friendly. It drastically reduces treatment time as it can be applied to surfaces still not completely dry.
- Highly resistant to light and heavy traffic.
- Weather resistant
- Treated surfaces are easier to clean.
- Does not alter terracotta frost resistance.

HOW TO USE IT

No dilution required: ready to use.

Application:

Shake before use. With the surface clean and dry, apply FILAPT10 evenly, using a large flat paintbrush, fleece applicator pad or roller, also working well into the grouting. As this is a water-based product, it stands up to residual humidity and can therefore even be applied just a few days after initial washing.

Apply a second coat of the product 2-3 hours later following the same method. Wait at least 12 hours before walking on the surface.

Maintenance: diluted solution of FILACLEANER.

Caution:

For surfaces with low absorbency (slate, Botticino or Carrara marble) we recommend diluting the product with water (1:1 dilution).

Do not use on polished surfaces.

Do not apply the product externally if rain is forecast.

If product has been wrongly applied or if a thorough cleaning is required, remove FILAPT10 using FILANOPAINT STAR.

COVERAGE

With one litre:

Terracotta Tuscan, rustic	15/20 m ²
Terracotta handmade, Spanish, hollow tile, brick	7/10 m ²
Stone	10/20 m ²

Coverage shown is for guidance purposes only and refers to single coats

Packaging

1 litre cans in boxes of 12.

5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
 - Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 5° to 30° C
The product must be applied to material with a temperature of between 10° and 30°C.

COMPOSITION

Product with a base of emulsions and synthetic waxes.

LABELLING

Signal words: Warning

Causes serious eye irritation.



Wash hands thoroughly after handling.
Wear protective gloves / protective clothing / eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice / attention.

TECHNICAL FEATURES

Appearance: liquid

Colour: milky white

Odour: typical of resin

Density: 1.023 kg/l

pH: 7.0

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.