



DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type :
Gyproc Plasterboards

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :
Gyproc WallBoard : 9.5mm, 12.5mm, 15mm
Gyproc SoundBloc : 12.5mm, 15mm
Gyproc FireLine : 12.5mm, 15mm
Gyproc DuraLine : 13.5mm, 15mm
Gyproc Moisture Resistant WallBoard : 12.5mm, 15mm
Gyproc Moisture Resistant Fireline : 12.5mm, 15mm
Gyproc WallBoard Premium : 12.5mm
Gyproc CoreBoard : 19mm
Gyproc Plank : 19mm
Gyproc WallBoard 4x2s : 9.5mm, 12.5mm
Gyproc WallBoard 8x2s : 12.5mm
Gyproc WallBoard 900mm wide : 12.5mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :
Plasterboard lining

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :
Gyproc Ireland
Registered in Ireland, Company No. 11815
Unit 14, Park West Industrial Park, Dublin 12
Tel : ++353 (0) 1 6298400

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4 generally
System 3 for Reaction to Fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The Building Test Centre, Notified body No. 1575 issued reports relating to System 3 classification requirements for reaction to fire

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. Declared performance :

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Shear strength	NPD	N/A
Reaction to fire	A2-s1, d0	EN 13501 - 1
Water vapour resistance factor	10	EN 12524
Flexural strength	Conforms	EN 520 : 2004 + A1:2009
Impact resistance	Performance declared is for the system of which the product is a part. Refer to Gyproc literature	
Direct airborne sound insulation		
Acoustic absorption		
Thermal conductivity	0.25 W/mk	EN 12524

10. The performance of the products identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Brian Dolan, Managing Director Gyproc Ireland

Park West Office 07 06 13
Place and Date of Issue

Signature

