

**Thompson's®**

# ONE COAT CONCRETE SEAL

## SEALS AND STABILISES CONCRETE IN ONE COAT

Garage floors take a battering from oil, fuel & car tyres. That's where Thompson's One Coat Concrete Seal comes in. In just one coat, it'll seal & stabilise garage floors and pathways.

- Stops concrete dusting
- Resists oil & fuel stains
- Stabilises and protects concrete surfaces

<b>Surfaces</b>	All concrete surfaces including garage floors, concrete pathways and driveways
<b>Coverage</b>	This 5 Litre tin will cover about 30m <sup>2</sup> in one coat – all depending on the texture & type of surface you're coating
<b>Dry Time</b>	About 4 hours. You can park your car on it after 8 hours
<b>Clean Up</b>	Clean all your equipment with White Spirit

### Before you start

- Give the concrete a decent scrub with a stiff bristle brush to get rid of any dust or dirt
- Open any windows or garage doors for ventilation
- Use Thompson's Oil & Drive Cleaner to give the concrete a good clean before application. For existing oil or grease stains use this neat
- Make sure any cleaners are rinsed off the concrete and it's dry before applying One Coat Concrete Seal

### Using One Coat Concrete Seal

- On cold and damp days drying and re-coat will take longer. For best results, use on a dry day above 10°C
- Give the tin a good stir
- Pour the tin into a roller tray and use a long pile roller to apply in long smooth strokes
- If you're sealing your garage floor, start from the furthest point and work towards the door – don't seal yourself into a corner!
- Apply an even coat, making sure that any puddles are spread into dry areas
- It's just one coat, so that's it, job done

FYI - For more porous concrete, you might need to apply a second coat after 4 hours

Sherwin-Williams Diversified Brands Limited  
Thorncliffe Park, Chapeltown, Sheffield S35 2YP

Tel: 0114 246 7171 (UK)

Tel: 00353 1 2135760 (Ireland)

[enquiry@thompsonsweatherproofing.co.uk](mailto:enquiry@thompsonsweatherproofing.co.uk)

Thompson's is a registered trademark of the  
Sherwin-Williams Company © 2015



5 010214 852758 >

**5 litre** e

C01536

