Technical data sheet DSTC / SSTC - TOOTHED PLATE TIMBER CONNECTOR





Single sided and double sided connector plates for enhanced bolt performance in timber. Conforms to BS EN 912: 1999 Annex C. Specification for toothed plate connectors.

UK-DoP-h10/0007

FEATURES

Material

• Pre-galvanised mild steel.



TECHNICAL DATA

SSTC - Single Sided Toothed Connector

	Dimensions				
References	Diameter [Dia]	Hole Diameter [mm]	Material t [mm]	Teeth Height [mm]	
	dc	d1	Materiai t [mm]		
SSTC50	48	12	1	6.6	
SSTC60	62	12	1.2	8.7	
SSTC75	75	16	1.3	10.4	

Single Sided Toothed Connector

DSTC - Double Sided Toothed Connector

	Dimensions				
References	Diameter [Dia]	Hole Diameter [mm]	Material t [mm]	Teeth Height [mm]	
	dc	d1	Materiai t [mm]		
DSTC50	48	16	1	13	
DSTC60	62	20	1.2	16	
DSTC75	75	26	1.3	19.5	

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 / fax: +44 1827 255616 Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®	DSTC / SSTC - Toothed Plate Timber Connector		page 1/2
	2017-11-06	www.strongtie.co.uk	



Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 / fax: +44 1827 255616 Information presented on this document is the exclusive property of Simpson Strong-Tie®	DSTC / SSTC - Toothed Plate Timber Connector		page 2/2
It is valid only when associated with products supplied by Simpson Strong-Tie®	2017-11-06	www.strongtie.co.uk	