according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard®-700 S

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead Watchmead

Hertfordshire AL7 1BQ

United Kingdom

Telephone : +44 (0) 1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Type of product : Mixture

# Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour. Specific target organ toxicity - single ex-H336: May cause drowsiness or dizziness.

posure, Category 3, Central nervous

svstem

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :









Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters air-

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



		H336 H411	ways. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
		P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
		P273	Avoid release to the environment.
		Response:	
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
		P331	Do NOT induce vomiting.
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Hazardous components which must be listed on the label:

919-446-0 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-

25%)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

# **Hazardous components**

Chemical Name CAS-No.	Classification (REGULATION (EC)	Concentration [%]
EC-No.	No 1272/2008)	
Registration number		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Flam. Liq.3; H226 STOT SE3; H336 STOT RE1; H372	>= 50 - <= 100
919-446-0 01-2119458049-33-XXXX [corresponding group CAS 64742-82-1]	Asp. Tox.1; H304 Aquatic Chronic2; H411	

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S

Revision Date 18.11.2015 Version 2.0 Print Date 18.11.2015

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** : Aspiration may cause pulmonary oedema and pneumonitis.

> Ervthema Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or

water courses.


5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S





Further information

Revision Date 18.11.2015

: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the

given occupational exposure limits (see section 8). For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when

handling chemical products

Advice on protection against : Use explosion-proof equipment. Keep away from

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



Revision Date 18.11.2015 Version 2.0 Print Date 18.11.2015

fire and explosion heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

**SECTION 8: Exposure controls/personal protection** 

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



Sika ®

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

### **Environmental exposure controls**

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : hydrocarbon-like

Odour Threshold : No data available

Flash point : ca. 30 °C

Ignition temperature : 235 °C

Lower explosion limit (Vol-%) : 0,6 %(V)

Upper explosion limit (Vol-%) : 6,5 %(V)

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : Note: Not applicable

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : 3,9997 hPa

Density : ca.0,8 g/cm3

at 20 °C

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S

Revision Date 18.11.2015 Version 2.0

: Note: insoluble Water solubility

Partition coefficient: n-

octanol/water

Viscosity, dynamic : No data available

Viscosity, kinematic : < 6,9 mm2/s

at 40 °C

: No data available

Relative vapour density : No data available

: No data available Evaporation rate

### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### Skin corrosion/irritation

### **Product:**

Remarks: Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S

Revision Date 18.11.2015

Version 2.0



# Serious eye damage/eye irritation

### **Product:**

Remarks: No data available

### Respiratory or skin sensitisation

### **Product:**

Remarks: No data available

# Germ cell mutagenicity

### **Product:**

Germ cell mutagenicity- As-

: No data available

# sessment

# Carcinogenicity

### **Product:**

Carcinogenicity - Assess- : No data available

ment

# Reproductive toxicity

### **Product:**

Reproductive toxicity - As-

sessment

: No data available

No data available

# **Aspiration toxicity**

### **Product:**

May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

# 12.2 Persistence and degradability

No data available

# 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S





### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

# **SECTION 14: Transport information**

**ADR** 

14.1 UN number: 126314.2 Description of the goods: PAINT14.3 Class: 314.4 Packing group: IIIClassification Code: F1Labels: 3

Tunnel restriction code : (D/E) **14.5 Environmentally hazard-** : yes

ous

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S

Revision Date 18.11.2015 Version 2.0 Print Date 18.11.2015



**IATA** 

14.1 UN number: 126314.2 Description of the goods: Paint14.3 Class: 314.4 Packing group: IIILabels: 314.5 Environmentally hazard-: yes

ous

**IMDG** 

**14.1 UN number** : 1263 **14.2 Description of the goods** : PAINT

(naphtha (petroleum))

 14.3 Class
 : 3

 14.4 Packing group
 : III

 Labels
 : 3

 EmS Number 1
 : F-E

 EmS Number 2
 : S-E

 14.5 Marine pollutant
 : yes

### 14.6 Special precautions for user

No data available

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Prohibition/Restriction**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Banned and/or restricted

(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-

25%))

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH Information: All substances contained in our Products are


- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

VOC-CH (VOCV) : 92,03 %

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



VOC-EU (solvent) : 92,03 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure. H372

H411 Toxic to aquatic life with long lasting effects.

# Full text of other abbreviations

Aquatic Chronic Chronic aquatic toxicity Aspiration hazard Asp. Tox. Flam. Liq. Flammable liquids

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

**ADR** Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

**GHS** Globally Harmonized System

International Air Transport Association **IATA** International Maritime Code for Dangerous Goods **IMDG** 

LC50

Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LD50 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

**MARPOL** International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

**OEL** Occupational Exposure Limit

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

according to Regulation (EC) No. 1907/2006

# Sikagard®-700 S



Revision Date 18.11.2015 Version 2.0 Print Date 18.11.2015

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!