

PRODUCT DATA SHEET

RONSEAL TRADE QUICK DRY INTERIOR VARNISH

Ronseal Trade Quick Dry Interior Varnish is available in a range of clear and coloured variants and is based on a unique blend of water based polymers to maximise performance and friendlier use. Ronseal Trade Quick Dry Interior Varnish gives a clear or coloured transparent finish that enhances the natural beauty of wood whilst providing long lasting protection to all interior woodwork. Ronseal Trade Quick Dry Interior Clear Varnish provides a non-yellowing finish for woodwork.

INTRODUCTION		CLEANING OF TOOLS
Ronseal Trade Quick Dry Interior Varnish provides a transparent finish which displays and highlights the rich, natural beauty of the wood. It is suitable for application to soft and hardwoods in interior situations. Ronseal Trade Quick Dry Interior Clear Varnish does not yellow woodwork. Ronseal Trade Quick Dry Interior Coloured Varnish provides a coloured finish which modifies the natural colour of wood.	Avoid the inhalation of dust when sanding, wear a suitable face mask or employ wet sanding techniques.	All equipment should be cleaned immediately after use with water and detergent.
Ronseal Trade Quick Dry Interior Varnish forms a tough, durable seal. It is resistant to knocks and scratches, and will withstand most household chemicals.	As Ronseal Trade Quick Dry Interior Varnish gives a transparent finish, any marks or blemishes in the substrate will show after treatment.	Remove as much product as possible from equipment prior to cleaning.
COMPOSITION	APPLICATION	REPAIR
Ronseal Interior Varnish is based on a unique blend of water based polymers and contains no hydrocarbon solvents.	Ronseal Trade Quick Dry Interior Varnish has been formulated for brush application. Always use a good quality, synthetic filament brush and stir the varnish thoroughly before and during use.	Damaged areas can be repaired by local applications of Ronseal Trade Quick Dry Interior Varnish and additional full coatings can be applied after long periods of use. Promote adhesion for repairs or additional coats by light abrasion, and wipe with a damp cloth.
PROPERTIES	IMPORTANT NOTES	
Appearance – Low viscosity milky/coloured liquid. VOC Content – Low (0.3-7.99% w/v). Odour – Low. Miscible with water.	Ronseal Trade Quick Dry Interior Varnish should be generously applied with the minimum of brushing, and finished in the direction of the grain. Do not overbrush - any milkiness will disappear, so overbrushing will adversely affect the finished result.	Wooden and metal surfaces particularly in pre-1960 buildings may have previously been treated with paint containing lead pigments. Special care must be taken when sanding or stripping. Professional decorators should carry out a COSHH assessment before any work is carried out. For further information consult our Technical Services Department.
FIELDS OF APPLICATION	Apply 3 coats leaving 1 hour between coats. Lightly sand with 240 grit paper and remove dust prior to application of the final coat.	Avoid the inhalation of dust when sanding, wear a suitable face mask or employ wet sanding techniques.
Ronseal Trade quick Dry Interior Varnish may be used for interior applications to all softwood and hardwood windows, skirtings, architraves and panelling etc.	Ronseal Trade Quick Dry Interior Varnish has a rapid drying time. Organise work to minimise wet edges.	Always conduct a test area to confirm colour suitability. The natural colour of the wood may affect the final colour achieved.
Ronseal Trade Quick Dry Interior Varnish is not suitable for use on floors. Use Ronseal Trade Ultra Tough Floor Varnish.	COVERAGE	Do not use Ronseal Interior Varnish when temperature is below 10°C or in high humidity.
PREPARATION	Up to 16 m² per litre per coat. Coverage will vary with absorbency of substrate.	Do not use wire wool when preparing surfaces for Ronseal Interior Varnish.
Ensure all surfaces are free from wax, grease and oil by wiping with a cloth dampened with white spirit.	DRYING TIME	Always stir varnishes thoroughly before and during use.
Sand smooth with 120 grit paper. Do not use steel wool. Remove dust with a damp cloth. Allow to dry thoroughly.	Ronseal Interior Varnish is touch dry in 20 minutes. Recoat after 1 hour. 100% cure in 24 hours.	If water is accidentally splashed onto the surface within 2-3 days of application,
	Poor ventilation, low temperatures, high humidity and porosity of the substrate will lengthen drying and re-coat times.	

simply remove by gently wiping with a soft cloth. Do not rub the wet surface.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. No smoking. Store upright and carefully reseal partly used containers.

The shelf life of the product in airtight containers is at least 3 years.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Non-flammable product.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

750 ml resealable containers.

DISPOSAL

Some local authorities have special facilities for the disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams Diversified
Brands Ltd
Thorncliffe Park
Chapelton
Sheffield
S35 2YP**

Tel: +44(0)114 246 7171
Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

MAY, 2017. ISSUE 1.