

# **CREOCOTE OIL BASED WOOD TREATMENT**

## **Product Information Sheet**

### **DESCRIPTION**

Bartoline Creocote is a non-Biocidal oil based wood treatment, effective when applied to exterior timbers such as garden sheds, fences and trellis work. The oil based properties provides excellent surface water repellence, restricts weather damage and improves grain definition.

### **PREPARATION**

Ensure that all timbers are structurally sound, dry and free from surface growths. Care should be taken to protect valuable plants and foliage during application. Children and pets should be kept away from treated timbers until they are completely dry.

Timbers previously treated with Creosote, Creosote Substitute or a solvent based wood preservative will readily accept re-treatment with Bartoline Creocote. Sealed or painted timbers must be stripped back to bare wood before coating with this product. The shade may vary from batch to batch and it is therefore recommended that containers with the same batch number are selected to ensure shade uniformity. Alternatively, premix different batches. The final shade is dependant upon the timber being treated and the previous covering applied. The colour will fade with time. To ensure suitability it is recommended that test patches are applied before general application.

### **APPLICATION**

Bartoline Creocote can be applied by brush, spray or dip methods.

A deeper colour may be attained by applying further treatments.

Apply liberally, soaking the timber to achieve best results.

Always ensure that end-grain timbers are fully saturated.

For timbers being set in the ground, apply Bartoline Bitumen Paint to protect against groundwater saturation.

### **COVERAGE**

Depending upon the texture and porosity of the timber to be treated, application of a single coat of Bartoline Creocote will cover at the rate of 1 litre per 6 to 8 square meters.

### **AFTER CARE**

Clean all tools and application equipment with Bartoline White Spirit.

### **SPECIFICATION**

<b>Physical State:</b>	Liquid
<b>Form/colour:</b>	Brown liquid
<b>Odour:</b>	Strong Aromatic
<b>Ph ( ) (Deg C):</b>	Not determined
<b>Boiling Point (Deg C)</b>	180 - 350
<b>Flashpoint</b>	>90 Deg C
<b>Auto flammability: (Deg C)</b>	500
<b>Density (20 Deg C):</b>	0.800 – 1.00
<b>Solubility In Water (20.00 Deg C)</b>	insoluble
<b>Miscibility:</b>	Miscible with most hydrocarbon products
<b>VOC Content:</b>	30g/l (3%)

## **HEALTH AND SAFETY**

See MSDS for full information

May be fatal if swallowed and enters airways.

Causes skin irritation.

Harmful if inhaled.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

## **Packing Specification**

<b>Product / Pack Size</b>	<b>Quantity per Carton</b>	<b>Cartons / Drums per Pallet.</b>
4 Litre HDPE Bottle	4	40
20 Litre Drum	-	32
205 Litre Drum		4

## **Customs Tariff Code**

2710 1948

## **SHIPPING CLASSIFICATION**

<b>UN Number</b>	3082
<b>Shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID NOS (Diesel Fuel)
<b>Class</b>	9
<b>Packing group</b>	III
<b>IMDG Code</b>	9
<b>CAS No</b>	Preparation
<b>Marine Pollutant</b>	Yes
<b>ADR Class</b>	9
<b>ADR Classification Code</b>	M6
<b>Emergency Action Code</b>	F-A, S-F
<b>Hazard Identification No</b>	90
<b>Limited Quantity Size</b>	5 litres