

## PRODUCT DATA SHEET

# RONSEAL FENCING STAIN

Ronseal Fencing Stain provides optimum colour and protection to rough sawn sheds and fences in one coat. Ronseal Fencing Stain provides an excellent waterproof barrier whilst its fade resistant pigments provide unrivalled colour performance. This unique formula enables either brush or spray application through the Ronseal Precision Power and Fence Sprayers, for speedy application, along with excellent protective qualities.

### INTRODUCTION

Ronseal Fencing Stain is specifically formulated to provide optimum protection and colour performance to rough sawn garden timber. The product can be brush applied or spray applied using Ronseal Precision Power and Fence Sprayers, which provide accurate and consistent coverage.

The blend of high quality pigments in Ronseal Fencing Stain provides long lasting protection to the substrate by limiting the damaging effects of UV light.

A one coat application of Ronseal Fencing Stain will transform new or weathered wood however a further coat can be applied where a deeper colour is required.

Ronseal Fencing Stain is shower proof in 1-2 hours and is safe to use with plants and animals and is available in a range of classic colours.

### COMPOSITION

Ronseal Fencing Stain contains a water soluble vinyl acetate copolymer incorporating organic and inorganic pigments.

### PROPERTIES

|                |                               |
|----------------|-------------------------------|
| Appearance     | Structured liquid, light gel. |
| Odour          | Low, typical acrylic.         |
| VOC content    | Low (0.30% to 7.99% w/v)      |
| Non-flammable. |                               |
| Water based.   |                               |

### FIELDS OF APPLICATION

Ronseal Fencing Stain is suitable for use on all rough sawn garden timber such as sheds, fences, trellises, gates and pergolas.

It can be applied to bare wood or wood previously stained, weathered, compatible product of a similar colour.

Ronseal Fencing Stain is not suitable for use on smooth planed wood, decking or garden furniture.

For wood in contact with the ground use a suitable wood preserver.

### PREPARATION

Ensure wood is clean and dry prior to application.

Remove any dirt, moss, fungal growth and lichen with a stiff brush.

The treatment of a test area to confirm colour suitability is recommended.

### APPLICATION

Do not apply in wet conditions or if rain is likely before the product dries. Do not apply at temperatures below 10°C or in high humidity.

Ronseal Fencing Stain is safe to use around plants and animals. If plants are splashed during application wipe clean with a damp cloth before the product dries. Pets should be kept away from treated areas until the product has thoroughly dried.

#### Brush:

Stir the product well before and during use. Load brush generously.

Apply a thin even coat, ensuring the colour is uniform; take care not to spread the product too far.

One coat is normally sufficient, if needed a second coat may be applied, allow 2 hours between coats.

#### Spray:

Ronseal Fencing Stain is designed for use with the Ronseal Precision Power and Fence Sprayers see instruction manuals for further details.

Stand with the sprayer nozzle approximately 23cm (9 inches) away from the timber and gently squeeze the trigger to begin spraying.

Keep the nozzle a constant distance away from the timber and spray horizontally across the full width of the panel, working down overlap the previous pass by 50%. Ensure that the vertical struts and edges are treated.

**Do not spray in windy conditions. Use cardboard or plastic to protect from overspray.**

### COVERAGE

With one coat 9 litres will cover up to 54 square metres (about 9 fence panels).

### DRYING TIME

Shower proof in 1-2 hours.

Absorbency of substrate, low temperatures and high humidity will lengthen the drying time.

### CLEANING OF TOOLS

All tools and equipment should be cleaned immediately after use by washing in water and detergent.

Remove as much product as possible from tools and equipment before washing.

Please see Ronseal Precision Sprayer instruction manual for further details.

#### **IMPORTANT NOTES**

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Always test a small area prior to full application to confirm colour suitability and level of adhesion. The final colour will be influenced by the texture, grain, colour, porosity and type of wood as well as the number of coats applied.

Do not apply in temperatures below 10°C or in conditions of high humidity or if rain is likely before the product has fully dried.

Do not use on surfaces treated with solvent based fence treatments unless they have aged for at least one month.

#### **STORAGE**

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers is at least three years.

#### **HEALTH AND SAFETY**

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

#### **FLAMMABILITY**

Non-flammable.

#### **SUPPLY**

Available from selected DIY retailers.

#### **SIZES**

Available in 9 litre re-sealable containers.

#### **DISPOSAL**

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

#### **LIABILITY**

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### **DATA SHEETS**

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams Diversified Brands Ltd**  
**Thorncliffe Park**  
**Chapelton**  
**Sheffield**  
**S35 2YP**

Tel: +44(0)114 246 7171

Fax: +44(0)114 245 5629

*Registered in England 2968830*

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)

Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

MAY, 2016. ISSUE 1.