

# CONSTRUCTION TIMBER PRESERVER

Larsen Construction Timber Preserver is a ready to use wood preservative for the prevention of damage to timber from blue stain, wet rot, dry rot and wood boring insects and their larvae. It's low odour microemulsion technology penetrates deeply into the wood to give long lasting protection. Construction Timber Preserver can be used on most construction timber and joinery such as doors, window frames, roof timbers, floorboards, joists, rafters, etc. It can be over painted, stained, varnished, or polished when dry if required.

**PREVENTS ROT & INSECT ATTACK**  
**QUICK DRYING**  
**LONG LASTING PROTECTION**  
**DEEP PENETRATING**



## TECHNICAL INFORMATION

PRODUCT INFORMATION	
FORM:	Milky Liquid
COLOUR:	Dries Clear
FLASH POINT:	N/A Non flammable
HAZARD INFORMATION:	Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.
CLEANING:	Clean tools, equipment, etc. using warm water.
PACKAGING:	1L, 5L and 25L
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protect from frost and store below 40°C. Store in a safe place away from food or feed stuffs.
SHELF LIFE:	Minimum 24 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
ACTIVE	CONTAINS Propiconazole 3.75g/L, IPBC 1.25g/L, Permethrin 1.25g/L
BS EN 335 USE CLASS :	UC2 (UC3 following over-coating)
APPLICATION RATE:	As preventative – 1L per 5sq m
APPLICATION METHOD:	Low pressure spray or brush
APPLICATION TEMPERATURE:	+5°C to +30°C
DRYING TIME:	1 hr
OVERCOAT:	24 hrs
UK AUTHORISATION	HSE 10129
ROI AUTHORISATION	PCS 98334

## **DIRECTIONS FOR USE**

### **PREPARATION**

Wood should be clean and free from wood dust, paint, varnish and other contaminants which may prevent penetration.

### **APPLICATION**

Apply by low pressure spray or brush at a rate of 200ml/m<sup>2</sup> or 1L per 5m<sup>2</sup>.

Product is touch dry in 1 hour depending on wood and ambient conditions.

Unprotected persons and animals should be kept away from treated areas for 48 hours or until dry.

Wood can be over coated after 24hrs if dry.

### **RESTRICTIONS**

**FOR USE ONLY AS A WOOD PRESERVATIVE.**

Apply by brush or low pressure spray. Preventative - Apply at a rate of 200ml/m<sup>2</sup>. (1L per 5 m<sup>2</sup>). Users must comply in full with all their legal responsibilities under The Control of Pesticide Regulations 1986 (as amended), including complying with all conditions of approval. This product is approved under The Control of Pesticides Regulations 1986 (as amended) for use as directed.

#### **READ ALL PRECAUTIONS BEFORE USE**

This material and its container must be disposed of in a safe way. Do not contaminate foodstuffs, eating utensils or food contact surfaces. Cover all water storage tanks before application. This material and its container must be disposed of in a safe way. Do not touch treated surfaces until dry. Hazardous to bees. Do not use on beehives or beekeeping equipment. Wash hands and exposed skin before meals and after use. Keep in a safe place.

### **QUALITY**

This product is manufactured in a plant controlled under an integrated management system third party certified to BS EN ISO 9001.