



REINA

DESIGNER RADIATOR



2020

ALUMINIUM RADIATORS

Alco Vertical	20	Elisa	93
Alco Horizontal	21	Elvina	76
Alpan Vertical	22	Elvina2	77
Alpan Horizontal	23	Felino	103
Anita	38	Fiore	64
Belva Vertical	16	Flat Vertical	52
Belva Horizontal	17	Flat Horizontal	53
Bolca Satin Bronze	34	Florina	90
Bolca Polished	36	Fondi	67
Bolca Satin Blue	35	Grace	82
Burton	37	Jesi	100
Casina Vertical	14	Lago 1 - Lago 2	78
Casina Horizontal	15	Line	65
Divale	29	Marco	94
Evie	24	Matera	92
Fano Satin Blue	26	Mirus	86
Fano Satin Bronze	27	Nardo	104
Fano Anthracite	28	Neva Chrome Vertical	68
Fermo Satin Bronze	30	Neva Chrome Horizontal	69
Fermo Satin Blue	31	Neva Vertical	48-49
Fermo Satin	32	Neva Horizontal	50
Miray	25	Nevah	51
Neval Vertical Double	6	Nola	96
Neval Horizontal Double	7	Osimo	70
Neval Vertical Single	8	Palmari	102
Neval Horizontal Single	9	Pavia	85
Polito Vertical	12	Pienza	71
Polito Horizontal	13	Polia	81
Vicari Vertical	18	Porte	75
Vicari Horizontal	19	Reflect	59
Veroli	33	Rezzo	74
Wave Vertical	10	Rione Single	62
Wave Horizontal	11	Rione Double	63

MILD STEEL RADIATORS

Albi	58	Riva	105
Aliano	95	Roda	54
Ancora	66	Round	60
Arbori	84	Sena	55
Breno	79	Sesia	91
Bonera Vertical	56	Slimline Vertical	44
Bonera Horizontal	57	Slimline Horizontal	45
Borgo	87	Serpe	80
Carpi	98	Serena	88
Colona Vertical	40-41	Teano	97
Colona Horizontal	42-43	Trento	99
Chisa	83	Todi	73
Claro	101	Tubes	61
Coneva Vertical	46	Vasto	89
Coneva Horizontal	47		
Dimaro	72		

TRADITIONAL RADIATORS

Alicia	107
Camden	109
Oxford	108
Victoria	106

TOWEL RAILS

Capo Chrome Flat & Curved	116
Diva	110-111
Diva Anthracite Flat	114
Diva Black Flat & Curved	113
Diva Latte Flat	115
Diva White	112

STAINLESS STEEL RADIATORS

Adena	146
Adora	133
Alento	125
Arden	142
Artena Single Polished	160
Artena Double Polished	161
Artena Single Brushed	162
Artena Double Brushed	163
Belbo	127
Bivano	134
Capelli	128
Cavo	150-151
Celico	132
Deno	147
Egna	137
Elvo	144
Entice	130
Eos	166
Flox Vertical Single	118
Flox Horizontal Single	119
Flox Vertical Double	120
Flox Horizontal Double	121
Grosso	122
Helin	148
Kreon	139
Lovere	129
Luna	164-165
Mina	143
Misa	124
Nerox Single Horizontal Polished	152
Nerox Double Horizontal Polished	153
Nerox Single Vertical Polished	154
Nerox Double Vertical Polished	155
Nerox Single Horizontal Brushed	156
Nerox Double Horizontal Brushed	157
Nerox Single Vertical Brushed	158
Nerox Double Vertical Brushed	159
Piazza	123
Pizzo	141
Ricadi	131
Riesi	138
Rima	136

Savio	126
Scalo	149
Sorento	140
Square	135
Troisi	145

ELECTRIC RADIATORS & TOWEL WARMERS

Arlec Aluminium Electric Radiator	168
Arnage Dry Electric	170
Capo Electric	180
Diva Chrome Flat Electric	174-175
Diva White Electric	176
Diva Anthracite Electric	177
Diva Latte Electric	178
Diva Black Electric	179
Orne Dry Electric	171
Optima Electric Radiator	169
Rance Dry Electric	172

VALVES

Valves	182-185
--------	---------

ACCESSORIES

Standard Heating Element	186
Thermostatic Heating Element	186
Touch Thermostatic Heating Element	186

RAL AND SPECIAL COLOURS

RAL Colours Chart	187
Special Colours Chart	188



WELCOME TO OUR BROCHURE

Welcome to REINA – the UK's leading supplier of designer radiators and heated towel rails.

Established in 2005 and still privately owned. REINA continues to design and create more products than any other company in this field. constantly leading the trend by combining the latest styles and functionality.

Everyone has their own sense of style and design. and that's why REINA has created a range of products that meets the needs of every interior style.


Whether it is timeless classics to the latest in energy efficient designs. our radiators are now one of the most sort after products here in the UK.

Over the years we have worked to create. no matter what. the perfect home environment when it comes to home heating.

We are driven to understand how the REINA products can transform interiors to meet the new fashion designs for the home and our key criteria are style. desirability. uniqueness. originality and innovation.

REINA adds excitement to the world of heating.

The REINA range of designer models are sure to encompass the perfect design for you. no matter what shape. style or size you are looking for and we will continue to remain at the forefront of designer radiators and towel rails.



Why choose an aluminium radiator?

They use very low water content, which mean they can heat up a lot quicker than other materials.

Will reduce your energy costs.

Lightweight and produce terrific heat outputs from even the smaller models.


Recycled Aluminium helps us all with our carbon footprint.

Perfect for ground source heat pumps

Supplied with a 5 Year Guarantee.

www.reinadesgn.co.uk

ALUMINIUM RADIATOR



white

anthracite

polished

NEVAL VERTICAL DOUBLE

Image shown 1800 X 522 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	286	286	55	94	C	7400	2170
1800	345	345	55	94	C	8880	2604
1800	404	404	55	94	C	10360	3038
1800	463	463	55	94	C	11840	3472
1800	522	522	55	94	C	13320	3906
TOWEL BAR IS AVAILABLE IN CHROME (individual price)							



white

anthracite

polished

NEVAL HORIZONTAL DOUBLE

Image shown 600 X 1171 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	404	404	55	94	C/E/D	3444	1010
600	581	581	55	94	C/E/D	4920	1443
600	817	817	55	94	C/E/D	6888	2020
600	994	994	55	94	C/E/D	8364	2453
600	1171	1171	55	94	C/E/D	9840	2886
600	1407	1407	55	94	C/E/D	11808	3463

Material
Aluminium

5

Year
GuaranteeNext Working
Day Delivery

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

ALUMINIUM RADIATOR

white

anthracite

polished



NEVAL VERTICAL SINGLE

Image shown 1800 X 463 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	286	286	34	73	C	4710	1381
1800	345	345	34	73	C	5652	1657
1800	404	404	34	73	C	6594	1934
1800	463	463	34	73	C	7536	2210
1800	522	522	34	73	C	8478	2486

TOWEL BAR IS AVAILABLE IN CHROME (individual price)



white

anthracite

polished

NEVAL HORIZONTAL SINGLE

Image shown 600 X 1407 anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	404	404	34	73	C/E/D	2198	645
600	581	581	34	73	C/E/D	3140	921
600	817	817	34	73	C/E/D	4396	1289
600	994	994	34	73	C/E/D	5338	1565
600	1171	1171	34	73	C/E/D	6280	1842
600	1407	1407	34	73	C/E/D	7536	2210

ALUMINIUM RADIATOR



white

anthracite



WAVE VERTICAL

Image shown 1800 X 412 double anthracite

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
SINGLE	1800	204	204	34	78	C	3336	978
	1800	412	412	34	78	C	6672	1957
	1800	204	204	68	112	C	5656	1659
	1800	412	412	68	112	C	11312	3317
DOUBLE								
TOWEL BAR IS AVAILABLE IN CHROME (individual price)								



ALUMINIUM RADIATOR



white

anthracite

WAVE HORIZONTAL

Image shown 600 X 1452 double white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	412	412	34	78	C/E/D	2224	652
600	620	620	34	78	C/E/D	3336	978
600	828	828	34	78	C/E/D	4448	1304
600	1036	1036	34	78	C/E/D	5560	1630
600	1244	1244	34	78	C/E/D	6672	1957
600	1452	1452	34	78	C/E/D	7784	2283
600	412	412	68	112	C/E/D	3768	1105
600	620	620	68	112	C/E/D	5652	1657
600	828	828	68	112	C/E/D	7536	2210
600	1036	1036	68	112	C/E/D	9420	2762
600	1244	1244	68	112	C/E/D	11304	3315
600	1452	1452	68	112	C/E/D	13188	3867

SINGLE

DOUBLE

ALUMINIUM RADIATOR



polished



POLITO VERTICAL

Image shown 1800 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	332	332	55	75	C	5698	1671
1800	416	416	55	75	C	7123	2089
1800	500	500	55	75	C	8547	2506
TOWEL BAR IS AVAILABLE IN CHROME (individual price)							



polished

POLITO HORIZONTAL

Image shown 600 X 1256

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	416	416	55	75	C/E/D	2376	697
600	584	584	55	75	C/E/D	3326	975
600	836	836	55	75	C/E/D	4752	1394
600	1004	1004	55	75	C/E/D	5702	1672
600	1256	1256	55	75	C/E/D	7128	2090
600	1424	1424	55	75	C/E/D	8078	2369

ALUMINIUM RADIATOR



- satin

white

anthracite



CASINA VERTICAL

Image shown 1800 X 565 double anthracite

DOUBLE SINGLE

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
DOUBLE	1800	280	280	34	65	C	4354	1277
	1800	375	375	34	65	C	5806	1703
	1800	470	470	34	65	C	7257	2128
	1800	565	565	34	65	C	8708	2554
SINGLE	1800	280	280	55	86	C	6706	1967
	1800	375	375	55	86	C	8941	2622
	1800	470	470	55	86	C	11176	3277
	1800	565	565	55	86	C	13410	3933
TOWEL BAR IS AVAILABLE IN CHROME, WHITE AND ANTHRACITE (individual price)								



CASINA HORIZONTAL

Image shown 600 X 1230 double white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	470	470	34	65	C/E/D	2420	710
600	660	660	34	65	C/E/D	3388	994
600	850	850	34	65	C/E/D	4356	1277
600	1040	1040	34	65	C/E/D	5322	1561
600	1230	1230	34	65	C/E/D	6290	1845
600	1420	1420	34	65	C/E/D	7259	2129
600	470	470	55	86	C/E/D	3727	1093
600	660	660	55	86	C/E/D	5218	1530
600	850	850	55	86	C/E/D	6708	1967
600	1040	1040	55	86	C/E/D	8196	2403
600	1230	1230	55	86	C/E/D	9687	2841
600	1420	1420	55	86	C/E/D	11179	3278

SINGLE
DOUBLE

ALUMINIUM RADIATOR




BELVA VERTICAL

Image shown 1800 X 516 double anthracite

DOUBLE SINGLE

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
DOUBLE	1800	308	308	34	68	C	3882	1138
	1800	412	412	34	68	C	5175	1518
	1800	516	516	34	68	C	6469	1897
	1800	308	308	55	89	C	5978	1753
	1800	412	412	55	89	C	7970	2337
	1800	516	516	55	89	C	9962	2921
TOWEL BAR IS AVAILABLE IN CHROME, WHITE AND ANTHRACITE (individual price)								





white

anthracite

BELVA HORIZONTAL

Image shown 600 x 1244 double white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	412	412	34	68	C/E/D	1726	506
600	620	620	34	68	C/E/D	2588	759
600	828	828	34	68	C/E/D	3450	1012
600	1036	1036	34	68	C/E/D	4312	1265
600	1244	1244	34	68	C/E/D	5175	1518
600	1452	1452	34	68	C/E/D	6038	1771
600	412	412	55	89	C/E/D	2658	779
600	620	620	55	89	C/E/D	3986	1169
600	828	828	55	89	C/E/D	5313	1558
600	1036	1036	55	89	C/E/D	6640	1947
600	1244	1244	55	89	C/E/D	7970	2337
600	1452	1452	55	89	C/E/D	9299	2727

SINGLE

DOUBLE

ALUMINIUM RADIATOR




VICARI VERTICAL

Image shown 1800 X 500 single white

DOUBLE SINGLE

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
	1800	300	300	34	65	C	4639	1360
	1800	400	400	34	65	C	6165	1808
	1800	500	500	34	65	C	7706	2260
	1800	300	300	55	86	C	7144	2095
	1800	400	400	55	86	C	9494	2784
	1800	500	500	55	86	C	11868	3480
TOWEL BAR IS AVAILABLE IN CHROME, WHITE AND ANTHRACITE (individual price)								



ALUMINIUM RADIATOR

VICARI HORIZONTAL

Image shown 600 X 1200 single anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	400	400	34	65	C/E/D	2566	752
600	600	600	34	65	C/E/D	3083	904
600	800	800	34	65	C/E/D	4109	1205
600	1000	1000	34	65	C/E/D	5138	1507
600	1200	1200	34	65	C/E/D	6165	1808
600	1400	1400	34	65	C/E/D	7194	2110
600	400	400	55	86	C/E/D	3166	928
600	600	600	55	86	C/E/D	4747	1392
600	800	800	55	86	C/E/D	6329	1856
600	1000	1000	55	86	C/E/D	7913	2321
600	1200	1200	55	86	C/E/D	9494	2784
600	1400	1400	55	86	C/E/D	11078	3249

SINGLE
DOUBLE

ALUMINIUM RADIATOR



ALCO VERTICAL

Image shown 1800 X 520 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	280	280	68	116	C	5756	1688
1800	400	400	68	116	C	8058	2363
1800	520	520	68	116	C	10360	3038



white

anthracite



ALCO HORIZONTAL

Image shown 600 X 1180 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	400	400	68	116	C/E/D	2686	788
600	580	580	68	116	C/E/D	3837	1125
600	820	820	68	116	C/E/D	5372	1575
600	1000	1000	68	116	C/E/D	6523	1913
600	1180	1180	68	116	C/E/D	7674	2250
600	1420	1420	68	116	C/E/D	9209	2701



Material
Aluminium



5 Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe centre measurement including valves add/subtract 90mm accordingly

ALUMINIUM RADIATOR



ALPAN VERTICAL

Image shown 1800 X 600 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	200	50	50	70	C/E/D	3598	1055
1500	300	50	50	70	C/E/D	5395	1582
1500	400	50	50	70	C/E/D	7192	2109
1500	500	50	50	70	C/E/D	8992	2637
1500	600	50	50	70	C/E/D	10789	3164
1800	200	50	50	70	C/E/D	4355	1277
1800	300	50	50	70	C/E/D	6534	1916
1800	400	50	50	70	C/E/D	8672	2543
1800	500	50	50	70	C/E/D	10806	3169
1800	600	50	50	70	C/E/D	12948	3797
TOWEL BAR IS AVAILABLE IN CHROME (individual price)							



ALPAN HORIZONTAL

Image shown 600 X 1200 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	400	50	50	70	C/E/D	2885	846
600	500	50	50	70	C/E/D	3604	1057
600	600	50	50	70	C/E/D	4310	1264
600	700	50	50	70	C/E/D	5030	1475
600	800	50	50	70	C/E/D	5739	1683
600	900	50	50	70	C/E/D	6455	1893
600	1000	50	50	70	C/E/D	7164	2101
600	1100	50	50	70	C/E/D	7881	2311
600	1200	50	50	70	C/E/D	8593	2520
600	1400	50	50	70	C/E/D	10019	2938
600	1600	50	50	70	C/E/D	11451	3358


ALUMINIUM RADIATOR

white

EVIE

Image shown 1842 X 400

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1442	240	268	65	115	C	3996	1172
1442	320	348	65	115	C	5329	1563
1442	400	428	65	115	C	6661	1953
1442	480	508	65	115	C	7993	2344
1842	240	268	65	115	C	4884	1432
1842	320	348	65	115	C	6512	1910
1842	400	428	65	115	C	8140	2387
1842	480	508	65	115	C	9768	2865



white

MIRAY

Image shown 580 X 1200

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
430	400	428	75	120	C/E/D	2432	713
430	640	668	75	120	C/E/D	3891	1141
430	800	828	75	120	C/E/D	4862	1426
430	1040	1068	75	120	C/E/D	6323	1854
430	1200	1228	75	120	C/E/D	7296	2140
580	400	428	75	120	C/E/D	3199	938
580	640	668	75	120	C/E/D	5118	1501
580	800	828	75	120	C/E/D	6397	1876
580	1040	1068	75	120	C/E/D	8317	2439
580	1200	1228	75	120	C/E/D	9596	2814

ALUMINIUM RADIATOR



FANO SATIN BLUE

Image shown 1500 X 485 blue

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
720	485	455	57	72	C/E/D	1650	484
1240	485	455	57	72	C/E/D	2750	806
1500	485	455	57	72	C/E/D	3300	968







blue




polished




satin



bronze



anthracite



white

FANO SATIN BRONZE

Image shown 1500 X 485 bronze




Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
720	485	455	57	72	C/E/D	1650	484
1240	485	455	57	72	C/E/D	2750	806
1500	485	455	57	72	C/E/D	3300	968

Material
Aluminium5 Year
GuaranteeNext Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

ALUMINIUM RADIATOR



FANO ANTHRACITE

Image shown 1500 X 485 anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
720	485	455	57	72	C/E/D	1650	484
1240	485	455	57	72	C/E/D	2750	806
1500	485	455	57	72	C/E/D	3300	968





white

anthracite

polished



ALUMINIUM RADIATOR

DIVALE

Image shown 1200 X 530 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	530	455	70-90	85-105	C/E/D	1610	472
1200	530	455	70-90	85-105	C/E/D	2415	708
1480	530	455	70-90	85-105	C/E/D	3220	944

Material Aluminium





5 Year Guarantee

Next Working Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL

ALUMINIUM RADIATOR



FERMO SATIN BRONZE

Image shown 1190 X 480 bronze

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
710	480	455	50	81	C/E/D	2150	630
1190	480	455	50	81	C/E/D	3440	1009
1550	480	455	50	81	C/E/D	4730	1387



ALUMINIUM RADIATOR

FERMO SATIN BLUE

Image shown 1190 X 480 blue

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
710	480	455	50	81	C/E/D	2150	630
1190	480	455	50	81	C/E/D	3440	1009
1550	480	455	50	81	C/E/D	4730	1387



Material
Aluminium



Year
Guarantee





Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

ALUMINIUM RADIATOR



FERMO SATIN

Image shown 1190 X 480 satin

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
710	480	455	50	81	C/E/D	2150	630
1190	480	455	50	81	C/E/D	3440	1009
1550	480	455	50	81	C/E/D	4730	1387





ALUMINIUM RADIATOR

VEROLI

Image shown 1550 X 480 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
750	480	455	62-82	100-120	C/E/D	2360	692
1190	480	455	62-82	100-120	C/E/D	3540	1038
1550	480	455	62-82	100-120	C/E/D	4425	1298



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL

ALUMINIUM RADIATOR



BOLCA SATIN BRONZE

Image shown 1530 X 485 bronze

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
870	485	455	57	72	C/E/D	2750	806
1200	485	455	57	72	C/E/D	3850	1129
1530	485	455	57	72	C/E/D	4950	1452





ALUMINIUM RADIATOR



BOLCA SATIN BLUE

Image shown 1530 X 485 blue

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
870	485	455	57	72	C/E/D	2750	806
1200	485	455	57	72	C/E/D	3850	1129
1530	485	455	57	72	C/E/D	4950	1452



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL

ALUMINIUM RADIATOR



BOLCA POLISHED

Image shown 1530 X 485 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
870	485	455	57	72	C/E/D	2750	806
1200	485	455	57	72	C/E/D	3850	1129
1530	485	455	57	72	C/E/D	4950	1452





ALUMINIUM RADIATOR

BURTON

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1180	485	455	68	116	C/E/D	5165	1515



Material
Aluminium

5

Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL



- white
- anthracite
- polished

ANITA

Image shown 1195 X 530 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
835	530	455	70-90	85-105	C/E/D	2151	631
1195	530	455	70-90	85-105	C/E/D	3585	1051
1510	530	455	70-90	85-105	C/E/D	4302	1262





Why choose a mild steel radiator?

A wide range of stunning designs from Towel warmers to Designer radiators that suit all budgets and trends.

A large selection of colours to choose from ranging from Chrome, White, Anthracite and a huge selection of RAL painted finishes. (see pages with RAL logo for more information)

With the added strength of steel they are popular throughout the household for their durability & style.

Supplied with a 5 Year Guarantee.

COLUMN RADIATOR



Image shown 3 column 1800 X 380 white



Optional insertable feet
Available for all column radiators

2 COLUMN COLONA VERTICAL

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	200	200	66	98	C	2238	656
1500	290	290	66	98	C	3352	983
1500	380	380	66	98	C	4477	1313
1800	200	200	66	98	C	2641	774
1800	290	290	66	98	C	3959	1161
1800	380	380	66	98	C	5282	1549






Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	200	200	68	118	C	3021	886
1500	290	290	68	118	C	4531	1329
1500	380	380	68	118	C	6041	1772
1800	200	200	68	118	C	3592	1053
1800	290	290	68	118	C	5387	1580
1800	380	380	68	118	C	7184	2107

RAL COLOURS CHART

REINA now offer 33 exciting RAL colour options on dedicated Radiators All finishes are powder coated and are available within 7 working days from point of order (subject to stock availability). Ral Painted Radiators are Non-Cancellable

							
1000 Green Beige	1001 Paille Beige	1013 Oyster White	1015 Light Ivory	2004 Pure Orange	5002 Ultramarine Blue	1036 Pearl Gold	2003 Pastel Orange
							
3002 Carmine Red	5015 Middle Sky Blue	3000 Flame Red	3001 Signal Red	6029 Mint Green	7015 Slate Grey	5003 Dark Sapphire Blue	3005 Wine Red
							
7032 Grey	7035 Pale Grey	6005 Light Moss	5005 Signal Blue	8003 Clay Brown	8017 Chocolate Brown	7016 Anthracite Grey	7030 Stone Grey
							
9002 Grey White	9005 Jet Black	7040 Window Grey	7042 Traffic Grey A	9006 White Aluminium	9007 Grey Aluminium	8019 Grey Brown	9001 Cream
							
1023 Traffic Yel							

SPECIAL COLOUR CHART

							
Ral 7033 Cement Grey Fine Texture	Ral 5009 Azure Blue Fine Texture	Anodic Brown Extra Mat Metallic	Anodic Sapphire Extra Smooth Metallic	RAL 9006 Bariton 1	RAL 9007 Bariton 2	Cast Iron Fine Texture Metallic	Anodic Gold Extra Matt Metallic
							
Timeless Rust Fine Texture	Oxide 1 Fine Texture Speckled	Oxide 2 Fine Texture Speckled	City Teraccotta Fine Texture Metallic	Gold Supreme Fine Texture Metallic	Anodic Bronze Extra Matt Smooth Metallic	RAL 9011 Graphite Black Fine Texture	RAL 1019 Grey Beige Fine Texture
							
Ral 1013 Oyster White Fine Texture	Ral 7015 Slate Grey Fine Texture	Grey Gold Matt Smooth Metallic	Noble Bronze Matt Smooth Metallic				

COLUMN RADIATOR



Optional insertable feet
Available for all column radiators
Image shown 3 column 600 X 1010 white



RAL & SPECIAL COLOURS
PAGE 187 & 188



2 COLUMN COLONA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
500	605	605	66	98	C/E/D	2540	745
500	785	785	66	98	C/E/D	3223	945
500	1010	1010	66	98	C/E/D	4300	1261
500	1190	1190	66	98	C/E/D	5081	1490
600	605	605	66	98	C/E/D	3022	886
600	785	785	66	98	C/E/D	3951	1159
600	1010	1010	66	98	C/E/D	5112	1499
600	1190	1190	66	98	C/E/D	6043	1772

3 COLUMN COLONA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
300	1010	1010	68	118	C/E/D	3603	1057
300	1190	1190	68	118	C/E/D	4257	1248
300	1370	1370	68	118	C/E/D	4912	1440
500	605	605	68	118	C/E/D	3501	1027
500	785	785	68	118	C/E/D	4579	1343
500	1010	1010	68	118	C/E/D	4926	1445
500	1190	1190	68	118	C/E/D	7005	2054
500	1370	1370	68	118	C	8081	2370
600	605	605	68	118	C/E/D	4136	1213
600	785	785	68	118	C/E/D	5387	1580
600	1010	1010	68	118	C/E/D	6972	2045
600	1190	1190	68	118	C/E/D	8241	2417
600	1370	1370	68	118	C	9508	2788

4 COLUMN COLONA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
300	1010	1010	94	163	C/E/D	4649	1363
300	1190	1190	94	163	C/E/D	5493	1611
300	1370	1370	94	163	C/E/D	6339	1859
500	605	605	94	163	C/E/D	4463	1309
500	785	785	94	163	C/E/D	5837	1712
500	1010	1010	94	163	C/E/D	7553	2215
500	1190	1190	94	163	C	8927	2618
500	1370	1370	94	163	C	10301	3021
600	605	605	94	163	C/E/D	5287	1550
600	785	785	94	163	C/E/D	6915	2028
600	1010	1010	94	163	C/E/D	8949	2624
600	1190	1190	94	163	C	10575	3101
600	1370	1370	94	163	C	12201	3578

MILD STEEL



Optional Extra : Height adjustable towel bar in chrome finish sold separately

anthracite

white



RAL & SPECIAL COLOURS
PAGE 187 & 188

SLIMLINE VERTICAL

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
470	300	50	30-55	62-87	C	977	287
770	300	50	30-55	62-87	C	1605	471
1170	300	50	30-55	62-87	C	2441	716
1170	400	50	30-55	62-87	C	3254	954
1170	500	50	30-55	62-87	C	4066	1192
1470	300	50	30-55	62-87	C	3069	900
1470	400	50	30-55	62-87	C	4089	1199
1470	500	50	30-55	62-87	C	5113	1499
1770	300	50	30-55	62-87	C	3694	1083
1770	400	50	30-55	62-87	C	4923	1444
1770	500	50	30-55	62-87	C	6154	1805

SLIMLINE CHROME 300/400/500 TOWEL BAR

Image shown 1770 X 500 white



RAL & SPECIAL COLOURS
PAGE 187 & 188

anthracite

white

SLIMLINE HORIZONTAL

Image shown 600 X 1000 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	400	400	30-55	62-87	C	1668	489
600	600	600	30-55	62-87	C	2506	735
600	800	800	30-55	62-87	C	3337	979
600	1000	1000	30-55	62-87	C	4175	1224
600	1200	1200	30-55	62-87	C	5005	1468
600	1400	1400	30-55	62-87	C	5843	1713

MILD STEEL

CONEVA VERTICAL

anthracite

white



RAL & SPECIAL COLOURS
PAGE 187 & 188

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	300	300	68	113	C	5031	1475
1500	370	370	68	113	C	6289	1844
1500	440	440	68	113	C	8547	2506
1500	510	510	68	113	C	8803	2582
1800	300	300	68	113	C	6036	1770
1800	370	370	68	113	C	7547	2213
1800	440	440	68	113	C	9055	2655
1800	510	510	68	113	C	10564	3098

Image shown 1800 X 440 white



anthracite

white

RAL & SPECIAL COLOURS
PAGE 187 & 188

CONEVA HORIZONTAL

Image shown 550 X 790 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
550	440	440	68	113	C/E/D	3233	948
550	580	580	68	113	C/E/D	4311	1264
550	790	790	68	113	C/E/D	5928	1738
550	1000	1000	68	113	C/E/D	7547	2213
550	1210	1210	68	113	C/E/D	9164	2687
550	1420	1420	68	113	C/E/D	10781	3162

MILD STEEL




Image shown 1800 X 295 double anthracite

NEVA VERTICAL SINGLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	236	236	65	103	C	2265	664
1500	295	295	65	103	C	2816	826
1500	354	354	65	103	C	3380	991
1500	413	413	65	103	C	3944	1157
1500	472	472	65	103	C	4508	1322
1500	531	531	65	103	C	5070	1487
1800	236	236	65	103	C	2717	797
1800	295	295	65	103	C	3380	991
1800	354	354	65	103	C	4055	1189
1800	413	413	65	103	C	4732	1388
1800	472	472	65	103	C	5408	1586
1800	531	531	65	103	C	6884	2019

NEVA VERTICAL DOUBLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1500	236	236	65	103	C	3420	1003
1500	295	295	65	103	C	4252	1247
1500	354	354	65	103	C	5104	1497
1500	413	413	65	103	C	5955	1746
1500	472	472	65	103	C	6807	1996
1500	531	531	65	103	C	7656	2245
1800	236	236	65	103	C	4103	1203
1800	295	295	65	103	C	5104	1497
1800	354	354	65	103	C	6123	1796
1800	413	413	65	103	C	7145	2095
1800	472	472	65	103	C	8166	2395
1800	531	531	65	103	C	10395	3048



can be used horizontal (brackets sold separately)
Horizontal brackets

white

anthracite



RAL & SPECIAL COLOURS
PAGE 187 & 188

MILD STEEL



NEVA HORIZONTAL

Image shown 550 X 1003 double white

SINGLE

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
550	413	413	413	65	103	C/E/D	1447	424
550	590	590	590	65	103	C/E/D	2066	606
550	826	826	826	65	103	C/E/D	2907	852
550	1003	1003	1003	65	103	C/E/D	3512	1030
550	1180	1180	1180	65	103	C/E/D	4131	1211
550	1416	1416	1416	65	103	C/E/D	4957	1454

DOUBLE

550	413	413	413	65	103	C/E/D	2.315	679
550	590	590	590	65	103	C/E/D	3306	969
550	826	826	826	65	103	C/E/D	4651	1364
550	1003	1003	1003	65	103	C/E/D	5619	1648
550	1180	1180	1180	65	103	C/E/D	6.610	1938
550	1416	1416	1416	65	103	C/E/D	7931	2326



RAL & SPECIAL COLOURS
PAGE 187 & 188

anthracite

white

NEVAH

Image shown 590 X 1000 double white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
295	1000	955	47	88	C	1792	526
295	1200	1155	47	88	C	2110	619
295	1400	1355	47	88	C	2441	716
590	600	555	47	88	C/E/D	2579	756
590	800	755	47	88	C/E/D	3036	890
590	1000	955	47	88	C/E/D	3578	1049
590	1200	1155	47	88	C/E/D	4.16	1236
590	1400	1355	47	88	C/E/D	4920	1443
295	1000	955	63	103	C	2796	820
295	1200	1155	63	103	C	3292	965
295	1400	1355	63	103	C	3807	1116
590	600	555	63	103	C/E/D	4023	1180
590	800	755	63	103	C/E/D	4737	1389
590	1000	955	63	103	C/E/D	5583	1637
590	1200	1155	63	103	C	6577	1929
590	1400	1355	63	103	C	7674	2250

SINGLE

DOUBLE

FLAT VERTICAL SINGLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1600	218	218	39	68	C	2113	620
1600	292	292	39	68	C	2818	826
1600	366	366	39	68	C	3522	1033
1600	440	440	39	68	C	4226	1239
1600	514	514	39	68	C	4930	1446
1800	218	218	39	68	C	2378	697
1800	292	292	39	68	C	3171	930
1800	366	366	39	68	C	3962	1162
1800	440	440	39	68	C	4755	1394
1800	514	514	39	68	C	5549	1627

FLAT VERTICAL DOUBLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1600	218	218	64	93	C	2684	787
1600	292	292	64	93	C	3578	1049
1600	366	366	64	93	C	4509	1322
1600	440	440	64	93	C	5509	1616
1600	514	514	64	93	C	6311	1851
1800	218	218	64	93	C	3092	907
1800	292	292	64	93	C	4123	1209
1800	366	366	64	93	C	5191	1522
1800	440	440	64	93	C	6230	1827
1800	514	514	64	93	C	7268	2131

Image shown 1800 X 440 double white



white

anthracite



RAL & SPECIAL COLOURS
PAGE 187 & 188

FLAT HORIZONTAL SINGLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	440	440	39	68	C/E/D	1661	487
600	588	588	39	68	C/E/D	2214	649
600	810	810	39	68	C/E/D	3044	893
600	1032	1032	39	68	C/E/D	3874	1136
600	1254	1254	39	68	C/E/D	4704	1379
600	1402	1402	39	68	C/E/D	5257	1542

FLAT HORIZONTAL DOUBLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	440	440	64	93	C/E/D	2407	706
600	588	588	64	93	C/E/D	3210	941
600	810	810	64	93	C/E/D	4413	1294
600	1032	1032	64	93	C/E/D	5617	1647
600	1254	1254	64	93	C/E/D	6822	2001
600	1402	1402	64	93	C/E/D	7824	2294

Image shown 600 X 1032 double white



white

anthracite



RAL & SPECIAL COLOURS
PAGE 187 & 188

MILD STEEL



anthracite

white



RODA

Image shown 590 X 1000 double white

DOUBLE SINGLE

	Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
							Btu	Watts
	590	600	555	47	101	C/E/D	2785	817
	590	800	755	47	101	C/E/D	3213	942
	590	1000	955	47	101	C/E/D	3944	1157
	590	1200	1155	47	101	C/E/D	4693	1376
	590	1400	1355	47	101	C/E/D	5476	1606
	590	600	555	82	136	C/E/D	4066	1192
	590	800	755	82	136	C/E/D	4838	1419
	590	1000	955	82	136	C/E/D	5758	1689
	590	1200	1155	82	136	C	6853	2010
	590	1400	1355	82	136	C	7994	2344



white

SENA

Image shown 550 X 990 black

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
550	395	395	65	130	C/E/D	1763	517
550	595	595	65	130	C/E/D	2644	775
550	790	790	65	130	C/E/D	3526	1034
550	990	990	65	130	C/E/D	4407	1292
550	1185	1185	65	130	C/E/D	5288	1551

MILD STEEL



BONERA VERTICAL

Image shown 1800 X 456 anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	324	324	65	100	C	3919	1149
1800	456	456	65	100	C	5452	1599



BONERA HORIZONTAL

Image shown 550 X 984 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
550	456	456	65	100	C/E/D	1665	488
550	588	588	65	100	C/E/D	2183	640
550	852	852	65	100	C/E/D	3217	943
550	984	984	65	100	C/E/D	3735	1095
550	1248	1284	65	100	C/E/D	4769	1399

MILD STEEL



anthracite

white



Optional Extra : Height adjustable towel bar in chrome finish sold separately

ALBI

Image shown 1790 X 500 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1790	500	50	30-55	62-87	C	4820	1413

TOWEL BAR IS AVAILABLE IN CHROME (individual price)



MILD STEEL

white

black

REFLECT

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	445	445	60	90	C	4560	1337



Material
Steel



Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe centre measurement including valves add/subtract 90mm accordingly

MILD STEEL



RAL & SPECIAL COLOURS
PAGE 187 & 188

white

ROUND SINGLE AND DOUBLE

Image shown 1800 X 413 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	65	119	C	3521	1033
1800	413	413	65	119	C	4929	1445
1800	295	295	65	119	C	5316	1559
1800	413	413	65	119	C	7443	2183



MILD STEEL


white

TUBES SINGLE AND DOUBLE

Image shown 1800 X 350 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	350	350	55	85	C	4086	1198
1800	350	350	55	85	C	6476	1899

MILD STEEL



RAL & SPECIAL COLOURS
PAGE 187 & 188

white

RIONE SINGLE

Image shown 544 X 1200 single

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
544	400	355	55	83	C/E/D	1388	407
544	600	555	55	83	C/E/D	2083	611
544	800	755	55	83	C/E/D	2777	814
544	1000	955	55	83	C/E/D	3471	1018
544	1200	1155	55	83	C/E/D	4167	1222
544	1400	1355	55	83	C/E/D	4861	1426



RAL & SPECIAL COLOURS
PAGE 187 & 188

white

RIONE DOUBLE

Image shown 544 X 1000 double


Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
544	400	355	78	107	C/E/D	2110	619
544	600	555	78	107	C/E/D	3166	928
544	800	755	78	107	C/E/D	4221	1238
544	1000	955	78	107	C/E/D	5276	1547
544	1200	1155	78	107	C	6334	1857
544	1400	1355	78	107	C	7389	2167

MILD STEEL



white

anthracite



FIORE

Image shown 1800 X 400 anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1790	400	400	35-55	68-88	C	3826	1122
1790	490	490	35-55	68-88	C	4862	1426
1790	590	590	35-55	68-88	C	5851	1716



MILD STEEL

white

anthracite

LINE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	490	490	35-55	68-88	C	5208	1527



Material
Steel

5

Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe centre measurement including valves add/subtract 90mm accordingly

MILD STEEL



ANCORA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	490	490	35-55	68-88	C	4946	1450




FONDI

Image shown 1229 X 600 white

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
855	500	50	30-55	62-87	C	2040	598
855	600	50	30-55	62-87	C	2351	689
1229	500	50	30-55	62-87	C	2901	851
1229	600	50	30-55	62-87	C	3330	977
1790	500	50	30-55	62-87	C	4185	1227
1790	600	50	30-55	62-87	C	4799	1407

MILD STEEL



NEVA CHROME

Image shown 1800 X 413

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	47	88	C	2534	743
1800	354	354	47	88	C	3041	892
1800	413	413	47	88	C	3547	1040



NEVA CHROME

Image shown 550 X 826

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
550	413	413	47	88	C/E/D	1084	318
550	590	590	47	88	C/E/D	1547	454
550	826	826	47	88	C/E/D	2159	633
550	1003	1003	47	88	C/E/D	2457	721
550	1180	1180	47	88	C/E/D	2853	837

MILD STEEL

chrome

OSIMO

Image shown 1800 X 290

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	290	290	61-76	105-120	C	2602	763
1800	430	430	61-76	105-120	C	3780	1109
1800	570	570	61-76	105-120	C	5027	1474

70



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly



PIENZA

Image shown 550 X 995

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
550	485	485	61-76	105-120	C/E/D	1341	393
550	655	655	61-76	105-120	C/E/D	1789	525
550	825	825	61-76	105-120	C/E/D	2237	656
550	995	995	61-76	105-120	C/E/D	2683	787
550	1165	1165	61-76	105-120	C/E/D	3131	918

Material
Steel

5

Year
GuaranteeNext Working
Day Delivery

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

MILD STEEL



white

anthracite

chrome



RAL & SPECIAL COLOURS
PAGE 187 & 188

DIMARO CHROME

Image shown 1760 X 620 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1760	620	620	61-76	99-114	C	4450	1305

DIMARO WHITE & ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1760	620	620	61-76	99-114	C	5340	1566



chrome

TODI


Image shown 1200 X 260

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	108	78	65-80	100-115	C/E/D	435	128
1200	108	78	65-80	100-115	C/E/D	640	188
800	260	230	65-80	100-115	C/E/D	884	259
1200	260	230	65-80	100-115	C/E/D	1293	379

MILD STEEL



chrome



REZZO

Image shown 1460 X 550

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
740	450	420	65-80	80-95	C/E/D	900	264
1100	450	420	65-80	80-95	C/E/D	1270	372
1460	450	420	65-80	80-95	C/E/D	1651	484
740	550	520	65-80	80-95	C/E/D	959	281
1100	550	520	65-80	80-95	C/E/D	1352	396
1460	550	520	65-80	80-95	C/E/D	1758	516

MILD STEEL



chrome

PORTE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1200	500	470	65-80	80-95	C/E/D	1973	579

 Material Steel

 5 Year Guarantee

 Next Working Day Delivery

 EN 442

MILD STEEL

chrome

ELVINA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
350	500	470	70-85	305-320	C	908	266



chrome

ELVINA2

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1000	500	470	70-85	305-320	C/E/D	1346	395

 Material
Steel

 5 Year
Guarantee

 Next Working
Day Delivery

 EN 442

MILD STEEL




LAGO 1

Image shown 450 X 600 lago 1

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
450	600	420	65-75	80-90	C/E/D	795	233

LAGO 2

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
450	600	420	65-75	80-90	C/E/D	998	293



BRENO

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
350	700	50	60-70	70-80	C	802	235



Material
Steel

5

Year
Guarantee



Next Working
Day Delivery



MILD STEEL



anthracite

chrome

SERPE CHROME

Image shown 510 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
270	500	500	65-80	80-95	C/E/D	567	166
510	500	500	65-80	80-95	C/E/D	970	284

SERPE ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
270	500	500	65-80	80-95	C/E/D	624	183
510	500	500	65-80	80-95	C/E/D	1067	313




white

anthracite

POLIA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
400	900	50	30-55	62-87	C	1670	490

MILD STEEL



can be mounted left or right hand side

GRACE CHROME

Image shown 1140 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
780	500	100	61-76	102-117	C/E/D	1210	355
1140	500	100	61-76	102-117	C/E/D	1710	501

GRACE ANTHRACITE AND WHITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
780	500	100	61-76	102-117	C/E/D	1419	416
1140	500	100	61-76	102-117	C/E/D	2023	593



CHISA CHROME




Image shown 1130 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
820	500	100	61-76	102-117	C/E/D	1419	416
1130	500	100	61-76	102-117	C/E/D	2021	593

CHISA ANTHRACITE AND WHITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
820	500	100	61-76	102-117	C/E/D	1815	532
1130	500	100	61-76	102-117	C/E/D	2418	709

MILD STEEL



ARBORI CHROME

Image shown 1510 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
820	500	450	61-76	102-117	C/E/D	1499	440
1130	500	450	61-76	102-117	C/E/D	2021	593
1510	500	450	61-76	102-117	C/E/D	2688	788

ARBORI WHITE AND ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
820	500	450	61-76	102-117	C/E/D	1815	532
1130	500	450	61-76	102-117	C/E/D	2418	709
1510	500	450	61-76	102-117	C/E/D	3227	946



chrome



MILD STEEL

PAVIA

Image shown 1650 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	455	40-60	80-100	C/E/D	1468	430
1200	500	455	40-60	80-100	C/E/D	2243	658
1650	500	455	40-60	80-100	C/E/D	3312	971
800	600	555	40-60	80-100	C/E/D	1664	488
1200	600	555	40-60	80-100	C/E/D	2499	733
1650	600	555	40-60	80-100	C/E/D	3628	1064



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 85

MILD STEEL



chrome

MIRUS

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
900	500	300	71-91	175-195	C/E/D	1727	506
1200	500	300	71-91	175-195	C/E/D	2229	654



MILD STEEL

chrome

BORG

Image shown 1300 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
814	500	50	61-76	165-180	C/E/D	1989	583
1300	500	50	61-76	165-180	C/E/D	2838	832

Material Steel

5 Year Guarantee

Next Working Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL 87

MILD STEEL



anthracite

chrome



SERENA CHROME

Image shown 1200 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	300	270	70-90	85-105	C/E/D	730	214
1200	300	270	70-90	85-105	C/E/D	1097	322
500	500	470	70-90	85-105	C/E/D	767	225
800	500	470	70-90	85-105	C/E/D	1218	357
1200	500	470	70-90	85-105	C/E/D	1828	536

SERENA ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	300	270	70-90	85-105	C/E/D	840	246
1200	300	270	70-90	85-105	C/E/D	1262	370
500	500	470	70-90	85-105	C/E/D	882	259
800	500	470	70-90	85-105	C/E/D	1401	411
1200	500	470	70-90	85-105	C/E/D	2102	616



chrome



MILD STEEL

VASTO

Image shown 1460 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
755	500	470	65-80	80-95	C/E/D	1461	428
1130	500	470	65-80	80-95	C/E/D	2193	643
1460	500	470	65-80	80-95	C/E/D	2884	846



MILD STEEL



anthracite

chrome

Can be mounted left or right hand side

FLORINA CHROME

Image shown 1235 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	100	70-85	105-120	C/E/D	1526	448
1235	500	100	70-85	105-120	C/E/D	2315	679
1525	500	100	70-85	105-120	C/E/D	3016	884

FLORINA ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	100	70-85	105-120	C/E/D	1755	515
1235	500	100	70-85	105-120	C/E/D	2662	781
1525	500	100	70-85	105-120	C/E/D	3468	1017

MILD STEEL



Can be mounted left or right hand side



chrome

SESIA

Image shown 1500 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
860	500	100	70-85	105-120	C/E/D	1938	568
1180	500	100	70-85	105-120	C/E/D	2539	745
1500	500	100	70-85	105-120	C/E/D	3326	975



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL 91

MILD STEEL



Can be mounted left or right hand side



chrome

anthracite

MATERA CHROME

Image shown 998 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
722	500	100	61-76	110-125	C/E/D	1248	366
998	500	100	61-76	110-125	C/E/D	1684	494
1412	500	100	61-76	110-125	C/E/D	2337	685

MATERA ANTHRACITE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
722	500	100	61-76	110-125	C/E/D	1435	421
998	500	100	61-76	110-125	C/E/D	1937	568
1412	500	100	61-76	110-125	C/E/D	2687	788



Can be mounted left or right hand side



chrome


ELISA

Image shown 1550 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1000	500	100	62-82	100-120	C/E/D	2269	665
1550	500	100	62-82	100-120	C/E/D	3481	1021



MILD STEEL



chrome



MARCO

Image shown 1100 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	468	61-76	137-152	C/E/D	1623	476
1100	500	468	61-76	137-152	C/E/D	2212	649
1400	500	468	61-76	137-152	C/E/D	2683	787



MILD STEEL

chrome

ALIANO

Image shown 1000 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
500	500	468	61-76	137-152	C/E/D	706	207
1000	500	468	61-76	137-152	C/E/D	1413	414



MILD STEEL

Can be mounted left or right hand side



chrome

NOLA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1400	600	110	78-93	148-163	C/E/D	3160	927



MILD STEEL

chrome

TEANO

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1300	600	100	78-93	148-163	C/E/D	2889	847

 Material Steel

 5 Year Guarantee

 Next Working Day Delivery

 EN 442

MILD STEEL

chrome

CARPI

Image shown 1300 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	300	268	61-76	77-92	C/E/D	1145	336
1200	300	268	61-76	77-92	C/E/D	1659	487
800	400	368	61-76	77-92	C/E/D	1526	448
1200	400	368	61-76	77-92	C/E/D	2212	649
950	500	468	61-76	77-92	C/E/D	1908	560
1300	500	468	61-76	77-92	C/E/D	2912	854



MILD STEEL

chrome

TRENTO

Image shown 1300 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
950	500	440	61-76	97-112	C/E/D	2337	685
1300	500	440	61-76	97-112	C/E/D	3357	984

 Material
Steel

 5 Year
Guarantee

 Next Working
Day Delivery

 EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 99

MILD STEEL



Can be mounted left or right hand side



JESI CHROME

Image shown 1400 X 600 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1000	500	75	29-44	64-79	C	1135	333
1400	600	75	29-44	64-79	C	1743	511

JESI ANTHRACITE

1000	500	75	29-44	64-79	C	1305	383
1400	600	75	29-44	64-79	C	2004	588

100



Material
Steel

5

Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

MILD STEEL

chrome

CLARO

Image shown 1200 X 300

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
900	300	100	41	310	C/E/D	1547	454
1200	300	100	41	310	C/E/D	2139	627
1600	300	100	41	310	C/E/D	2788	818

MILD STEEL



anthracite

chrome



PALMARI CHROME

Image shown 900 X 500 chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
900	500	100	70-90	95-115	C/E/D	1109	325

PALMARI ANTHRACITE

900	500	100	70-90	95-115	C/E/D	1220	358
-----	-----	-----	-------	--------	-------	------	-----




MILD STEEL

FELINO

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
775	500	100	70-85	107-122	C/E/D	1918	562
1200	500	100	70-85	107-122	C/E/D	2770	812

MILD STEEL



NARDO

Image shown 1200 X 550

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
813	450	418	61-76	77-92	C/E/D	959	281
1200	450	418	61-76	77-92	C/E/D	1320	387
813	550	518	61-76	77-92	C/E/D	1080	317
1200	550	518	61-76	77-92	C/E/D	1476	433



MILD STEEL

chrome

RIVA

Image shown 1300 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
620	500	450	70-85	85-100	C/E/D	1490	437
960	500	450	70-85	85-100	C/E/D	2300	674
1300	500	450	70-85	85-100	C/E/D	3225	946



TRADITIONAL



chrome

VICTORIA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
960	675	528	92	230	C	5452	1599

chrome

ALICIA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
952	479	348	92	230	C	3431	1006



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

TRADITIONAL



chrome

OXFORD

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
960	538	393	134	175	C	4105	1204



chrome

CAMDEN

Image shown 508 X 770

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
508	680	680	50	230	C	2427	712
508	770	770	50	230	C	3013	884

 Material
Steel

 5 Year
Guarantee

 Next Working
Day Delivery

 EN 442

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe centre measurement including valves add/subtract 90mm accordingly

TOWEL RAIL



chrome

Image shown 1200 X 500 curved

25_{mm}
TUBES



DIVA - 25mm TOWEL RAIL

CHROME FLAT

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
600	300	260	70-85	85-100	25	C/E/D	680	199
800	300	260	70-85	85-100	25	C/E/D	820	240
1200	300	260	70-85	85-100	25	C/E/D	1438	422
1600	300	260	70-85	85-100	25	C/E/D	1982	581

CHROME FLAT & CURVED OPTIONS

800	400	360	70-85	85-100	25	C/E/D	1035	304
1000	400	360	70-85	85-100	25	C/E/D	1508	442
1200	400	360	70-85	85-100	25	C/E/D	1980	581
1600	400	360	70-85	85-100	25	C/E/D	2460	721
1800	400	360	70-85	85-100	25	C	2710	795
800	450	410	70-85	85-100	25	C/E/D	1103	323
1200	450	410	70-85	85-100	25	C/E/D	2082	611
1800	450	410	70-85	85-100	25	C	2988	876
800	500	460	70-85	85-100	25	C/E/D	1238	363
1000	500	460	70-85	85-100	25	C/E/D	1721	505
1200	500	460	70-85	85-100	25	C/E/D	2205	647
1400	500	460	70-85	85-100	25	C/E/D	2489	730
1600	500	460	70-85	85-100	25	C/E/D	2870	842
1800	500	460	70-85	85-100	25	C	3310	971
800	600	560	70-85	85-100	25	C/E/D	1363	400
1000	600	560	70-85	85-100	25	C/E/D	1860	545
1200	600	560	70-85	85-100	25	C/E/D	2385	699
1400	600	560	70-85	85-100	25	C/E/D	2752	807
1600	600	560	70-85	85-100	25	C/E/D	3121	915
1800	600	560	70-85	85-100	25	C	3556	1043
800	750	710	70-85	85-100	25	C/E/D	1534	450
1200	750	710	70-85	85-100	25	C/E/D	2570	754
1800	750	710	70-85	85-100	25	C	3852	1130



MODAL TRV
Corner Chrome Valve



MODAL TRV
Straight Chrome Valve



MODAL TRV
Angled Chrome Valve



white



DIVA WHITE

Image shown 1200 X 500

FLAT

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
800	300	260	70-85	85-100	25	C/E/D	820	240
1200	300	260	70-85	85-100	25	C/E/D	1438	422

FLAT & CURVED

800	400	360	70-85	85-100	25	C/E/D	1035	304
1200	400	360	70-85	85-100	25	C/E/D	1980	581
1800	400	360	70-85	85-100	25	C	2710	795
800	500	460	70-85	85-100	25	C/E/D	1238	363
1200	500	460	70-85	85-100	25	C/E/D	2205	647
1800	500	460	70-85	85-100	25	C	3310	971
800	600	560	70-85	85-100	25	C/E/D	1363	400
1200	600	560	70-85	85-100	25	C/E/D	2385	699
1800	600	560	70-85	85-100	25	C	3556	1043





DIVA BLACK FLAT & CURVED OPTIONS

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
800	400	360	70-85	85-100	25	C/E/D	1035	304
1200	400	360	70-85	85-100	25	C/E/D	1980	581
1800	400	360	70-85	85-100	25	C/E/D	2710	795
800	500	460	70-85	85-100	25	C/E/D	1238	363
1200	500	460	70-85	85-100	25	C/E/D	2205	647
1800	500	460	70-85	85-100	25	C	3310	971
800	600	560	70-85	85-100	25	C/E/D	1363	400
1200	600	560	70-85	85-100	25	C/E/D	2385	699
1800	600	560	70-85	85-100	25	C	3556	1043



DIVA ANTHRACITE FLAT

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
800	400	360	70-85	85-100	25	C/E/D	1035	304
1200	400	360	70-85	85-100	25	C/E/D	1980	581
1800	400	360	70-85	85-100	25	C/E/D	2710	795
800	500	460	70-85	85-100	25	C/E/D	1238	363
1200	500	460	70-85	85-100	25	C/E/D	2205	647
1800	500	460	70-85	85-100	25	C	3310	971
800	600	560	70-85	85-100	25	C/E/D	1363	400
1200	600	560	70-85	85-100	25	C/E/D	2385	699
1800	600	560	70-85	85-100	25	C	3556	1043



DIVA LATTE FLAT

Image shown 1800 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
800	400	360	70-85	85-100	25	C/E/D	1035	304
1200	400	360	70-85	85-100	25	C/E/D	1980	581
1800	400	360	70-85	85-100	25	C/E/D	2710	795
800	500	460	70-85	85-100	25	C/E/D	1238	363
1200	500	460	70-85	85-100	25	C/E/D	2205	647
1800	500	460	70-85	85-100	25	C	3310	971
800	600	560	70-85	85-100	25	C/E/D	1363	400
1200	600	560	70-85	85-100	25	C/E/D	2385	699
1800	600	560	70-85	85-100	25	C	3556	1043



CAPO CHROME FLAT & CURVED OPTIONS

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Tube Diameter mm	Fuel Type	Heat Outputs	
							Btu	Watts
800	400	355	70-85	85-100	22mm	C/E/D	914	268
1000	400	355	70-85	85-100	22mm	C/E/D	1171	343
1200	400	355	70-85	85-100	22mm	C/E/D	1312	384
1600	400	355	70-85	85-100	22mm	C/E/D	1734	508
800	500	455	70-85	85-100	22mm	C/E/D	1081	317
1000	500	455	70-85	85-100	22mm	C/E/D	1343	393
1200	500	455	70-85	85-100	22mm	C/E/D	1548	453
1600	500	455	70-85	85-100	22mm	C/E/D	2044	599
800	600	555	70-85	85-100	22mm	C/E/D	1253	367
1000	600	555	70-85	85-100	22mm	C/E/D	1516	444
1200	600	555	70-85	85-100	22mm	C/E/D	1795	526
1600	600	555	70-85	85-100	22mm	C/E/D	2371	695



Why choose a stainless steel radiator?

Stainless steel is a high quality material which does not rust so perfect for those luxurious wet room bathrooms.

It's an efficient conductor of heat which retains the heat for longer once you switch your heating system off.

Perfect finishes in Polished for bathrooms, bedrooms & Living rooms and Brushed effect to compliment any appliances within your kitchen area.

Supplied with a 25 Year Guarantee.

www.reinadesgn.co.uk

STAINLESS STEEL



polished

satin

FLOX VERTICAL SINGLE

Image shown 1800 X 472 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	69	107	C	3211	942
1800	354	354	69	107	C	3852	1130
1800	413	413	69	107	C	4495	1318
1800	472	472	69	107	C	5139	1507
1800	531	531	69	107	C	5780	1695





polished

satin

FLOX HORIZONTAL SINGLE

Image shown 600 X 1003 satin

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	69	107	C/E/D	1498	439
600	590	590	69	107	C/E/D	2141	628
600	826	826	69	107	C/E/D	2997	879
600	1003	1003	69	107	C/E/D	3690	1082
600	1180	1180	69	107	C/E/D	4283	1256

Material
Stainless Steel

25

Year
GuaranteeNext Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly



STAINLESS STEEL

polished

satin

FLOX VERTICAL DOUBLE

Image shown 1800 X 413 satin

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	69	107	C	4881	1431
1800	354	354	69	107	C	5857	1718
1800	413	413	69	107	C	6832	2004
1800	472	472	69	107	C	7811	2291
1800	531	531	69	107	C	8787	2577

120



Material
Stainless Steel

25

Year
Guarantee




Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly



FLOX HORIZONTAL DOUBLE

Image shown 600 X 1180 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	69	107	C/E/D	2397	703
600	590	590	69	107	C/E/D	3426	1005
600	826	826	69	107	C/E/D	4796	1406
600	1003	1003	69	107	C/E/D	5827	1709
600	1180	1180	69	107	C/E/D	6851	2009

STAINLESS STEEL



polished

can be mounted left or right hand side

GROSSO

Image shown 1250 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
850	500	50	65	130	C/E/D	1213	356
1250	500	50	65	130	C/E/D	1685	494
1650	500	50	65	130	C/E/D	2166	635





PIAZZA

Image shown 1670 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
870	500	50	65	130	C/E/D	1250	367
1270	500	50	65	130	C/E/D	1737	509
1670	500	50	65	130	C/E/D	2233	655



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL



STAINLESS STEEL

polished



MISA

Image shown 1450 X 530

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
720	530	500	50-60	67-77	C/E/D	1056	310
1120	530	500	50-60	67-77	C/E/D	1609	472
1450	530	500	50-60	67-77	C/E/D	2078	609



polished



ALENTO

Image shown 530 X 1120

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
720	530	500	50-60	245-255	C/E/D	1316	386
1120	530	500	50-60	245-255	C/E/D	1868	548
1450	530	500	50-60	245-255	C/E/D	2337	685



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

STAINLESS STEEL



SAVIO

Image shown 500 X 1360

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	470	50-60	67-77	C/E/D	1139	334
1080	500	470	50-60	67-77	C/E/D	1530	449
1360	500	470	50-60	67-77	C/E/D	1921	563





STAINLESS STEEL

BELBO

Image shown 1540 X 530

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
820	530	500	50-60	147	C/E/D	1303	382
1180	530	500	50-60	147	C/E/D	1878	551
1540	530	500	50-60	147	C/E/D	2449	718



Material
Stainless Steel

25 Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

STAINLESS STEEL

polished

Can be mounted left or right hand side

CAPELLI

Image shown 1235 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	50	80-95	105-120	C/E/D	1611	472
1235	500	50	80-95	105-120	C/E/D	2461	722
1525	500	50	80-95	105-120	C/E/D	3008	882





Can be mounted left or right hand side



polished

LOVERE

Image shown 1230 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
690	500	50	80-95	105-120	C/E/D	1173	344
960	500	50	80-95	105-120	C/E/D	1817	533
1230	500	50	80-95	105-120	C/E/D	2531	742



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 129

STAINLESS STEEL



ENTICE

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
770	500	50	80-95	105-120	C/E/D	2305	676
1200	500	50	80-95	105-120	C/E/D	3598	1055
1700	500	50	80-95	105-120	C/E/D	5183	1520





STAINLESS STEEL

Can be mounted left or right hand side

polished

RICADI

Image shown 1140 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
840	500	50	80-95	105-120	C/E/D	2404	705
1140	500	50	80-95	105-120	C/E/D	3188	935
1440	500	50	80-95	105-120	C/E/D	3890	1141



Material
Stainless Steel

25

Year
Guarantee




Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 131

STAINLESS STEEL




Can be mounted left or right hand side

CELICO

Image shown 1000 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
585	500	50	80-95	125-140	C/E/D	1044	306
1000	500	50	80-95	125-140	C/E/D	2088	612
1415	500	50	80-95	125-140	C/E/D	2954	866





Can be mounted left or right hand side



STAINLESS STEEL

polished

ADORA

Image shown 1106 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	500	50	80-95	125-140	C/E/D	2723	799
1106	500	50	80-95	125-140	C/E/D	3632	1065



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 133

STAINLESS STEEL



polished

BIVANO

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
300	800	50	105-120	140-155	C	1213	356





polished

SQUARE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
450	450	50	105-120	140-155	C	747	219

STAINLESS STEEL



polished



RIMA

Image shown 1260 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
780	500	50	105-120	140-155	C	1487	436
1020	500	50	105-120	140-155	C	1983	582
1260	500	50	105-120	140-155	C	2478	727
1500	500	50	105-120	140-155	C	2974	872



*polished***EGNA**

Image shown 1495 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
775	500	50	80-95	95-110	C	1341	393
1255	500	50	80-95	95-110	C	2420	710
1495	500	50	80-95	95-110	C	2959	868

Material
Stainless Steel25 Year
GuaranteeNext Working
Day Delivery

STAINLESS STEEL



RIESI

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1200	600	50	80-95	155-170	C/E/D	2818	826





STAINLESS STEEL

polished

KREON

Image shown 1160 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
780	500	460	85-100	120-135	C/E/D	2602	763
1160	500	460	85-100	120-135	C/E/D	3223	945



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN

442

STAINLESS STEEL



polished



SORENTO

Image shown 1106 X 600 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
800	600	50	80-95	125-140	C/E/D	2859	838
1106	600	50	80-95	125-140	C/E/D	3815	1119





STAINLESS STEEL

PIZZO

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1000	600	50	80-95	125-140	C/E/D	2192	643



Material
Stainless Steel

25

Year
Guarantee




Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 141

STAINLESS STEEL



polished

brushed



ARDEN

Image shown 1000 X 500 brushed

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
500	500	470	80-95	95-110	C/E/D	867	254
1000	500	470	80-95	95-110	C/E/D	1704	500





polished

brushed

MINA

Image shown 1170 X 480 brushed

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
750	480	440	80-95	95-110	C/E/D	1208	354
1170	480	440	80-95	95-110	C/E/D	1884	552



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN

442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 143

STAINLESS STEEL



polished



ELVO

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
660	530	500	50-60	264-274	C/E/D	1346	395



STAINLESS STEEL

polished

TROISI

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
294	532	462	67	300	C	708	208



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

STAINLESS STEEL



polished

ADENA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1300	532	462	67	300	C/E/D	3253	954





DENO

Image shown 1488 X 500 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
496	500	450	60-75	100-115	C/E/D	850	249
992	500	450	60-75	100-115	C/E/D	1648	483
1488	500	450	60-75	100-115	C/E/D	2269	665



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 147

STAINLESS STEEL



polished




HELIN

Image shown 1120 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
826	500	450	60-75	100-115	C/E/D	2045	600
1120	500	450	60-75	100-115	C/E/D	2863	840
1535	500	450	60-75	100-115	C/E/D	3688	1082





STAINLESS STEEL



SCALO

Image shown 1535 X 500 polished

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
826	500	50	60-75	100-115	C/E/D	2045	600
1120	500	50	60-75	100-115	C/E/D	2863	840
1535	500	50	60-75	100-115	C/E/D	3688	1082



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL 149

STAINLESS STEEL



Image shown 1230 X 500 polished



Can be mounted left or right hand side



Cavo

A stunning Designer Radiator made from a quality stainless steel that will offer you a practical solution to all your heating requirements and add style and luxury to your bathroom.

Supplied in Four size options & Two finishes.

Polished & Brushed , with the added 25 year guarantee as standard and being very competitively priced.

Cavo proves why it's the first choice from most of our customers.

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
530	500	50	60-75	100-115	C/E/D	985	289
880	500	50	60-75	100-115	C/E/D	1526	448
1230	500	50	60-75	100-115	C/E/D	1929	566
1580	500	50	60-75	100-115	C/E/D	2722	798




polished



brushed

STAINLESS STEEL



NEROX SINGLE

Image shown 600 X 826 single

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	65	103	C/E/D	1577	462
600	590	590	65	103	C/E/D	2254	661
600	826	826	65	103	C/E/D	3155	925
600	1003	1003	65	103	C/E/D	3884	1139
600	1180	1180	65	103	C/E/D	4508	1322





polished

NEROX DOUBLE

Image shown 600 X 826 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	65	103	C/E/D	2523	740
600	590	590	65	103	C/E/D	3606	1057
600	826	826	65	103	C/E/D	5048	1480
600	1003	1003	65	103	C/E/D	6134	1799
600	1180	1180	65	103	C/E/D	7212	2115



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

STAINLESS STEEL

NEROX SINGLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	65	103	C	3380	991
1800	354	354	65	103	C	4055	1189
1800	413	413	65	103	C	4732	1388
1800	472	472	65	103	C	5409	1586
1800	531	531	65	103	C	6084	1784

polished

Image shown 1800 X 413 single



NEROX DOUBLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	65	103	C	5138	1507
1800	354	354	65	103	C	6165	1808
1800	413	413	65	103	C	7192	2109
1800	472	472	65	103	C	8222	2411
1800	531	531	65	103	C	9249	2712

polished

Image shown 1800 X 413 double



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

STAINLESS STEEL



brushed

NEROX SINGLE

Image shown 600 X 826 single

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	65	103	C/E/D	1577	462
600	590	590	65	103	C/E/D	2254	661
600	826	826	65	103	C/E/D	3155	925
600	1003	1003	65	103	C/E/D	3884	1139
600	1180	1180	65	103	C/E/D	4508	1322





brushed

NEROX DOUBLE

Image shown 600 X 826 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	413	413	65	103	C/E/D	2523	740
600	590	590	65	103	C/E/D	3606	1057
600	826	826	65	103	C/E/D	5048	1480
600	1003	1003	65	103	C/E/D	6134	1799
600	1180	1180	65	103	C/E/D	7212	2115



Material
Stainless Steel

25 Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

STAINLESS STEEL

NEROX SINGLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	65	103	C	3380	991
1800	354	354	65	103	C	4055	1189
1800	413	413	65	103	C	4732	1388
1800	472	472	65	103	C	5409	1586
1800	531	531	65	103	C	6084	1784

brushed

Image shown 1800 X 413 single





NEROX DOUBLE

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
1800	295	295	65	103	C	5138	1507
1800	354	354	65	103	C	6165	1808
1800	413	413	65	103	C	7192	2109
1800	472	472	65	103	C	8222	2411
1800	531	531	65	103	C	9249	2712

brushed

Image shown 1800 X 413 double



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL

For pipe centre measurement including valves add/subtract 90mm accordingly

STAINLESS STEEL



polished

ARTENA SINGLE

Image shown 590 X 1000 single

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
590	400	360	65	103	C/E/D	1719	504
590	600	560	65	103	C/E/D	2579	756
590	800	760	65	103	C/E/D	3439	1009
590	1000	960	65	103	C/E/D	4298	1260
590	1200	1160	65	103	C/E/D	5158	1513





polished

ARTENA DOUBLE

Image shown 590 X 1000 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
590	400	360	65	103	C/E/D	2383	699
590	600	560	65	103	C/E/D	4023	1180
590	800	760	65	103	C/E/D	5364	1573
590	1000	960	65	103	C	6706	1967
590	1200	1160	65	103	C	8047	2360



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL 161

STAINLESS STEEL

brushed

ARTENA SINGLE

Image shown 590 X 1200 single

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
590	400	360	65	103	C/E/D	1719	504
590	600	560	65	103	C/E/D	2579	756
590	800	760	65	103	C/E/D	3439	1009
590	1000	960	65	103	C/E/D	4298	1260
590	1200	1160	65	103	C/E/D	5158	1513





brushed

ARTENA DOUBLE

Image shown 590 X 1200 double

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
590	400	360	65	103	C/E/D	2383	699
590	600	560	65	103	C/E/D	4023	1180
590	800	760	65	103	C/E/D	5364	1573
590	1000	960	65	103	C	6706	1967
590	1200	1160	65	103	C	8047	2360



Material
Stainless Steel

25

Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL 163

STAINLESS STEEL



polished

Image shown 1200 X 500



LUNA FLAT

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
600	300	268	50-60	65-70	C/E/D	881	258
720	350	318	50-60	65-70	C/E/D	1346	395
1200	350	318	50-60	65-70	C/E/D	2384	699
1500	350	318	50-60	65-70	C/E/D	2799	821
430	500	468	50-60	65-70	C/E/D	970	284
720	500	468	50-60	65-70	C/E/D	1935	567
1200	500	468	50-60	65-70	C/E/D	2660	780
1500	500	468	50-60	65-70	C/E/D	3544	1039
430	600	568	50-60	65-70	C/E/D	1109	325
720	600	568	50-60	65-70	C/E/D	2088	612
1200	600	568	50-60	65-70	C/E/D	3166	928
1500	600	568	50-60	65-70	C/E/D	3749	1099



The new range of the Luna and Eos stainless steel towel rails are now polished to a superior standard and feature an elegant design tube arrangement which looks perfect at home in a contemporary or traditional bathroom.

With both models now made in a heavier grade of stainless steel to ensure not just the best quality but you receive the assurance of a 25 year guarantee against manufacturing defect. making these two models the best available stainless steel towel rails in the market.

Consideration has even been given to the design of air vent arrangement. there are no more unsightly air vents on the back of the towel rail and the possibility of venting the system water onto the wall. the new design of air vent is now incorporated and concealed into the top of each towel rail and covered with a perfectly finish screwed on stainless steel cap which completely makes Luna and Eos the answer to your bathroom.

STAINLESS STEEL



polished



EOS

Image shown 1500 X 500

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs	
						Btu	Watts
430	500	468	50-60	75-85	C/E/D	970	284
720	500	468	50-60	75-85	C/E/D	1935	567
1200	500	468	50-60	75-85	C/E/D	2660	780
1500	500	468	50-60	75-85	C/E/D	3544	1039
430	600	568	50-60	75-85	C/E/D	1109	325
720	600	568	50-60	75-85	C/E/D	2088	612
1200	600	568	50-60	75-85	C/E/D	3166	928
1500	600	568	50-60	75-85	C/E/D	3749	1099





Why choose an electric radiator?

From Towel Warmers to Designer Radiators , standard and thermostatically controlled, Electric radiators are the perfect solution to heat your room without the added need to attach to your heating system.

Simply connected to a mains supply, our vast range of Electric radiators can prove to be an ideal and cheaper solution for your home.

ARLEC ALUMINIUM ELECTRIC RADIATOR

- Manufactured from Aluminium - Silent Operation
- Choice of output
- Slimline - 54mm deep
- Digital timer display
- Multiple modes - Frost protection. Economy. Comfort
- Remote control
- Wall mounted or floor standing (feet included)
- Plug fitted
- This product conforms to european Ecodesign directive (2009/125/EC) Lot 20



ARLEC ELECTRIC RADIATOR

Image shown 565 X 870

Overall Height mm	Dimension Width mm	Depth mm	Fuel Type	Heat Outputs Watts
565	414	54	E	700
565	490	54	E	900
565	642	54	E	1250
565	718	54	E	1500
565	870	54	E	1800

OPTIMA ELECTRIC RADIATOR

- IP 24
- 7 Day Timer
- Wall - mounted
- Electronic thermostat
- Open window function
- Safety thermal cut out
- External cable length 1.3m
- Low-temperature heating element
- This product conforms to european Ecodesign directive (2009/125/EC) Lot 20



OPTIMA ELECTRIC RADIATOR

Image shown 450 X785

Overall Height mm	Dimension Width mm	Depth mm	Fuel Type	Heat Outputs Watts
450	450	120	E	500
450	530	120	E	1000
450	660	120	E	1500
450	785	120	E	2000



ARNAGE DRY ELECTRIC

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Wall Distance mm	Fuel Type	Heat Outputs Watts
800	500	116	E	90
1200	500	116	E	130



ORNE DRY ELECTRIC

Overall Height mm	Dimension Width mm	Wall Distance mm	Fuel Type	Heat Outputs Watts
760	580	116	E	50



Material
Stainless Steel

2

Year
Guarantee



Next Working
Day Delivery

C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL



polished

RANCE DRY ELECTRIC

Overall Height mm	Dimension Width mm	Wall Distance mm	Fuel Type	Heat Outputs Watts
475	500	116	E	80





25^{mm}
TUBES



Thermostatic Touch



Thermostatic Remote



Standart Element

Image shown 1400 X 500

DIVA CHROME ELECTRIC

CHROME FLAT & CURVED OPTIONS

Our collection of ladder rails will enhance the overall appearance of any room in the home

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
600	300	85-100	25	100	300
800	300	85-100	25	150	300
1200	300	85-100	25	250	600
1600	300	85-100	25	400	600
800	400	85-100	25	150	300
1000	400	85-100	25	250	300
1200	400	85-100	25	250	300
1600	400	85-100	25	250	300
800	450	85-100	25	250	300
1200	450	85-100	25	400	600
800	500	85-100	25	250	300
1000	500	85-100	25	250	300
1200	500	85-100	25	400	600
1400	500	85-100	25	400	600
1600	500	85-100	25	600	600
800	600	85-100	25	250	300
1000	600	85-100	25	250	300
1200	600	85-100	25	400	600
1400	600	85-100	25	400	600
1600	600	85-100	25	600	600
800	750	85-100	25	250	300
1200	750	85-100	25	400	600



DIVA WHITE ELECTRIC

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
800	300	85-100	25	150	300
1200	300	85-100	25	250	600
800	400	85-100	25	150	300
1200	400	85-100	25	400	600
800	500	85-100	25	250	300
1200	500	85-100	25	400	600
800	600	85-100	25	250	300
1200	600	85-100	25	400	600



DIVA ANTHRACITE ELECTRIC

Image shown 1200 X 600

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
800	400	85-100	25	150	300
1200	400	85-100	25	400	600
800	500	85-100	25	250	300
1200	500	85-100	25	400	600
800	600	85-100	25	250	300
1200	600	85-100	25	400	600



latte



Thermostatic Touch

Thermostatic Remote

Standart Element

DIVA LATTE ELECTRIC

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
800	400	85-100	25	150	300
1200	400	85-100	25	400	600
800	500	85-100	25	250	300
1200	500	85-100	25	400	600
800	600	85-100	25	250	300
1200	600	85-100	25	400	600



black



Thermostatic Touch



Thermostatic Remote



Standard Element


DIVA BLACK ELECTRIC

Image shown 1200 X 500

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
800	400	85-100	25	150	300
1200	400	85-100	25	400	600
800	500	85-100	25	250	300
1200	500	85-100	25	400	600
800	600	85-100	25	250	300
1200	600	85-100	25	400	600



C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL



Thermostatic Touch



Thermostatic Remote




Standart Element

CAPO ELECTRIC

Image shown 1200 X 500 chrome

Overall Height mm	Dimension Width mm	Wall Distance mm	Tube Diameter mm	Heat Output watts Standard	Heat Output watts Thermostatic
800	400	70-85	55-75	22mm	300
1200	400	70-85	55-75	22mm	600
1600	400	70-85	55-75	22mm	600
800	500	70-85	55-75	22mm	300
1200	500	70-85	55-75	22mm	600
1600	500	70-85	55-75	22mm	600
800	600	70-85	55-75	22mm	300
1200	600	70-85	55-75	22mm	600
1600	600	70-85	55-75	22mm	600





Valves, Accessories and Elements.

Radiator valves and elements are not only a part of your essential heating requirements for your system, but they also offer the same aesthetics as the radiator can do to your room.

Please browse our comprehensive list of valves and elements for the perfect complement to your Reina Designer Radiator.

VALVES



Portland
Angled Chrome Valve



Portland
Angled Brushed Valve



Portland
Angled White Valve



Portland
Angled Anthracite Valve



Portland
Chrome Straight Valve



Portland
Brushed Straight Valve



Portland
Straight White Valve



Portland
Straight Anthracite Valve



Crova
Chrome Corner Valve



Crova
Corner Brushed Valve



Crova
Corner White Valve



Crova
Corner Anthracite Valve



LOGE
Angled Chrome Valve



LOGE
Angled Brushed Valve



LOGE
Angled Anthracite Valve



LOGE
Straight Chrome Valve



LOGE
Straight Brushed Valve



LOGE
Straight Anthracite Valve



MODAL TRV
Corner Brushed Valve



MODAL TRV
Straight Brushed Valve



MODAL TRV
Angled Brushed Valve



MODAL TRV
Corner Bronze Valve



MODAL TRV
Straight Bronze Valve



MODAL TRV
Angled Bronze Valve

VALVES



MODAL TRV
Corner Chrome Valve



MODAL TRV
Straight Chrome Valve



MODAL TRV
Angled Chrome Valve



MODAL TRV
Corner Black Valve



MODAL TRV
Straight Black Valve



MODAL TRV
Angled Black Valve



MODAL TRV
Corner Oiled Bronze Valve



MODAL TRV
Straight Oiled Bronze Valve



MODAL TRV
Angled Oiled Bronze Valve



MODAL TRV
Corner Anthracite Valve



MODAL TRV
Straight Anthracite Valve



MODAL TRV
Angled Anthracite Valve



MODAL TRV
Corner White Valve



MODAL TRV
Straight White Valve



MODAL TRV
Angled White Valve



Surrey
Angled Chrome Valve



Bronte
Traditional Angled Valve



Bronte
Traditional Straight Valve



T-Piece Chrome
(Dual Fuel)




T-Piece White
(Dual Fuel)



T-Piece Anthracite
(Dual Fuel)



Chrome Pipe Kit
(200mm)



MODAH Twin "H" Type TRV (suitable for 50mm Pipe Centres)
Available Colour Options : White, Anthracite and Chrome
Model Version Options : Angled or Straight

Note : All models supplied with removeable cover guard.



Thermostatic Heating Element

Remote Control included. 7 day programmable electronic thermostat. Selectable between room temperature and water temperature.
Open window detection build-in.
Rotatable display for horizontal or vertical use
Available in three power options - 300w. 600w. 900w



Touch Thermostatic Heating Element

Available in: 300 (watts), 600 (watts), 900 (watts). (With Cable Cover)




Optional white cap for standard element

Standard Heating Element

This product does not conform to European Ecodesign Directive (2009/125/EC) Lot 20 and should not be used to warm a room

Available in: 100(watts)

150 (watts)
250 (watts)
400 (watts)
600 (watts)
800 (watts)



Liquid Filling for Electric Only Models



Towel Hook (pair)

RAL COLOURS CHART

REINA now offer 33 exciting RAL colour options on dedicated Radiators

All finishes are powder coated and are available within 7 working days from point of order (subject to stock availability). Ral Painted Radiators are Non-Cancellable



1000 Green Beige



1001 Pale Beige



1013 Oyster White



1015 Light Ivory



2004 Pure Orange



5002 Ultramarine Blue



1036 Pearl Gold



2003 Pastel Orange



3002 Carmine Red



5015 Middle Sky Blue



3000 Flame Red



3001 Signal Red



6029 Mint Green



7015 Slate Grey



5003 Dark Sapphire Blue



3005 Wine Red



7032 Grey



7035 Pale Grey



6005 Light Moss



5005 Signal Blue



8003 Clay Brown



8017 Chocolate Brown



7016 Anthracite Grey



7030 Stone Grey



9002 Grey White



9005 Jet Black



7040 Window Grey



7042 Traffic Grey A



9006 White Aluminum



9007 Grey Aluminium



8019 Grey Brown



9001 Cream



1023 Traffic Yellow



Available Within 7 - 10 Working Days

SPECIAL RAL COLOURS

All finishes are powder coated and are available within 7 working days from point of order (subject to stock availability). Ral Painted Radiators are Non-Cancellable



RAL 7033 CEMENT GREY
FINE TEXTURE



RAL 5009 AZURE BLUE
FINE TEXTURE



ANODIC BROWN EXTRA
MAT METALLIC



ANODIC SAPPHIRE EXTRA
SMOOTH METALLIC



RAL 9006 BARITON 1



RAL 9007 BARITON 2




CAST IRON FINE TEXTURE
METALLIC



ANODIC GOLD EXTRA
MATT METALLIC



TIMELESS RUST FINE
TEXTURE



OXIDE 1 FINE TEXTURE
SPECKLED




OXIDE 2 FINE TEXTURE
SPECKLED




CITY TERACCOTTA
FINE TEXTURE METALLIC



GOLD SUPREME FINE
TEXTURE METALLIC




ANODIC BRONZE EXTRA
MATT SMOOTH METALLIC




RAL 9011 GRAPHITE
BLACK FINE TEXTURE



RAL 1019 GREY BEIGE
FINE TEXTURE



RAL 1013 OYSTER WHITE
FINE TEXTURE



RAL 7015 SLATE GREY
FINE TEXTURE



GREY GOLD MATT
SMOOTH METALLIC



NOBLE BRONZE MATT
SMOOTH METALLIC



TERMS & CONDITIONS

Terms

These conditions of Sale are expressly incorporated as terms of any orders, which we accept or other conditions proposed by the Buyer will not apply to the Contract unless expressly accepted in writing to the seller. The Seller reserves the right to charge interest on late payments in line with the late payment of commercial debts act. All other accounts must be settled at the time of order.

Delivery

All quoted dispatched/delivery dates are given bona fide, and are such as we expect to achieve and every effort will be made to adhere to them. The Seller shall not accept any liability for failure to despatch within such a time. Time for dispatch shall be extended for a reasonable time if delay is caused by instructions or lack of instructions from you. Despatch time maybe extended during holiday periods and company shut downs.

Please note:-

- Packaging is free and non returnable
- Delivery is to the nearest hard stand area
- The consignee is responsible for off-loading the goods
- The goods must be checked and signed for in the presence of the carrier
- Any damages and shortages must be reported in writing within two working days of delivery
- Failure to comply with any of the above may invalidate any claims
- We recommend that after you check the product on delivery that it is stored in its packaging to prevent damage.
- Atay Global cannot accept responsibility for items damaged after delivery.

Atay Global will ensure that goods are delivered in good order and cannot accept any responsibility for any claims that occur after delivery.

Signing of the delivery note will be determined as acceptance that goods have been delivered in good order at the time of delivery.

Carriage Charges

All prices are inclusive of carriage charges within the mainland of the United Kingdom. Exceptions are as follows Northern Ireland, Highlands of Scotland and Isles off the United Kingdom and Scotland, these areas carry a delivery charge premium. Please ask for a quotation and delivery timings. Please note: All valves and accessories carry a £5 low order delivery fee if ordered without a radiator.

Guarantee and Liability

Where the Seller is not the manufacturer of the goods we will use reasonable endeavours to make over to the Buyer the benefit of any warranty or guarantee given by the manufacturer. The guarantee is offered subject to the goods being installed, operated by incorrect use and installed by a competent approved installer. Any alterations to the specification using non-approved parts or correct installation shall invalidate the guarantee.

The seller shall have sole discretion deciding to replace or repair an item which agreed faulty. In cases of replacement the Company reserves the right to offer the nearest equivalent product where the original is not available.

The Sellers liability is limited to the repair or supply of replacement product and does not include cost incurred in effecting a replacement.

Under no circumstances will the Seller or his servants, agents or subcontractors be liable for any loss or damage of any kind whatsoever, (except arising from death or personal injury) whether consequential or otherwise caused directly or indirectly by any negligence on the Sellers part or part of any of the seller servants, agents or subcontractors in connection with or arising out of the manufacture or supply of the goods or in connection with any advice or statement given or made by or on the sellers behalf.

Cancellations

Orders cannot be cancelled except with the Seller's consent and on terms that will indemnify the Seller against loss.

Return of goods

Only in exceptional circumstances and by previous agreement with the seller will the Seller accept back for credit items that have been supplied against confirmed orders, providing the goods to be returned are new and adequately packed and unused. The net value of the goods returned will be credited to the buyer subject to a restocking fee.

Samples & Displays

All goods supplied for samples and displays are subject to agreed discounts and are for display only (and are NOT FOR RESALE) remain the property of the Seller until paid in full.

All heat outputs are shown at $\Delta T70C$. in compliance BSEN442 - All dimensions are given as an indication only.

These products conform to European Ecodesign Directive (2009/125/EC) Lot 20

NOTES



Atay Global Ltd. Unit 6. Weybridge Farm. Stambourne Road.
Great Yeldham. Essex. CO9 4RB
Tel: 01787 238540 | Fax: 01787 237991
www.reinadesign.co.uk | info@atayglobal.com

In the interest of continuing design, development and product development, we reserve the right to change colours, designs and product specifications or method of manufacture. Such changes may be made without prior notice and without incurring any obligation. Indications of the colourways throughout this brochure are as accurate as photographic and print processes will allow. This brochure does not form part of a contract of sale. e&oe