



MSS

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	MSS
Product Range	Wall Ties
Product Sub-range	Wallstarters
Product Type	Multi Starter
Test Standard	BBA Specification
Notified Body	Lucideon Ltd (NB 1289)
Material	Stainless Steel 1.4301 to BS EN10088-2:2014
Coating/Finish/Colour	Mill Finish
Length 1/Projection	100mm Tie Projection

Length 2/height	2x 1155mm Lengths
Width/Wing Length	40mm
Material Gauge	0.6mm
Individual Weight (kg)	0.931
Declared Loadbearing Capacity	6kN (ULS) per 1.155m length
Fire Rating	Euroclass A1
Fixing Hole Dimensions	18 x 5.5mm Slots
Fixing Type	M6x50 Hex Head Coach Screws A2 Stainless Steel (Supplied)
Installation requirement 1	Locate starter above DPC level
Installation requirement 2	Drill/plug existing wall as per instructions. Fix using supplied fixings.
Installation requirement 3	Use 1 tie per block course or 3 brick courses (225mm)
Installation requirement 4	Bed/cover ties in fresh mortar, pressing tie down until it makes contact with block below
Unit of Sale EAN	5014316025812
Sales Qty	12
Packaging material	Cardboard
Carton Ref	XBCMULTICTN
Carton/Size	1185 x 190 x 90
Packaging weight	0.353
Packaged transit weight	11.525
Features/Benefits 1	Rapid connection of a new wall to existing without cutting out and toothing/bonding in
Features/Benefits 2	Individual "Turn & Slide" ties accommodate all sizes of brick and block
Features/Benefits 3	Suitable for all wall thicknesses from 60-250mm

HEALTH AND SAFETY INFORMATION

1. Identification

'Expamet'
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition

Stainless Steel 1.4301 to BS EN10088-2:2014

3. Hazards Identification

Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures

Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures

Non-flammable material.

6. Accidental release measures

Not applicable.

7. Handling and storage

Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8. Exposure controls

Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties

Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity

Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information

High temperatures can produce fumes.

12. Ecological information

No known Hazard.

13. Disposal considerations

Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information

Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.